

3 2 10 11	Found recent stone mound with 3"x4"x30" post and recent attention poster. Possible remnants of old stone mound. No evidence of original BT's. Blazed lines to north, east, & south; 1941 location posters referenced to the corner (also older tag, 1932±); Testimony by DAVID L KING (operator of adjacent Placer Claims to NW & SW) that corner had been at the present location when he was a young man in ± 1932, indicate corner has been accepted in present location for at least 42 years. A double proportioned corner would fall S79°1'51" W, 49 29'. ACCEPTED corner location and SET 1"x48" IP 36" in ground with 1 1/2" Brass Cap marked: T22N RII E Raised rock mound 36" diameter by 12" high. Established new BT's which bear from corner: S3 S2 PP 13" DBH N36°W 18.6' Scribed S3 BT, Tagged LS3848 1974 SP 20" DBH N 8° E 45.5' Scribed S2 BT, Tagged LS3848 LS 3848 WF 11" DBH S52°E 30.5' Scribed S11 BT, Tagged LS3848 WF 12" DBH S75°W 6.5' Scribed S10 BT, Tagged LS3848	1/4 27 34	Found remnants of rock mound from which bears: DF snag 50" DBH N 71°E 11.9' to face, 14.2' to center, "X" chopped on south side, 1941 BRC location poster (RI) Spruce 38° N71°E 11.9' IC down 19" DBH S71°E 21.7' ± 1930 Location poster (RI) IC 15" S71°E 21.8' SET 1"x36" IP 28" in ground with 1 1/2" Brass Cap marked: T23N RII E Rebuilt rock mound 36" diameter by 15" high from which 1/4 S27 established new BT's bears: S34 IC 5" DBH S38°E 11.6' Scribed 1/4 S34 BT, Tagged LS3848 1974 WF 7" DBH N83°W 20.2' Scribed 1/4 S27 BT, Tagged LS3848 LS 3848	SI/16 34 35	SET 1"x48" IP 34" in ground with 1 1/2" Brass Cap marked: T23N RII E Raised rock mound 36" diameter by 15" high from which bears: WF 9" DBH S70°W 17.8' Scribed 1/16 BT, Tagged LS 3848 S34 S35 1974 WF 10" DBH S8°E 23.2' Scribed 1/16 BT, Tagged LS 3848 LS 3848 1/2" Rebar with yellow plastic cap stamped RCE III 173 bears S 37°50'47"E 12.32' (R/S 4-17)
1/4 10 11	Found original BT, second BT and corner apparently destroyed by logging. Re-established corner from existing BT and SET 1"x36" IP 26" in ground with 1 1/2" Brass Cap marked: T22N RII E Raised rock mound 36" diameter by 12" high from which bears: WF 27" DBH S 3° W 23.6' Scribed 1/4 S10 BT, Tagged LS3848 S10 S11 1974 IC 12" DBH N 78° E 31.1' Scribed 1/4 S11 BT, Tagged LS3848 LS 3848 WF 17" DBH S65°W 19.8' Scribed 1/4 S BT, Tagged LS3848 (RI) Fir 5" dia S65°W 19.8'	1/4 33 34	Found 1/4 corner stone in rock mound. Stone 11"x10"x17", (RI) 15x15x6, marked 1/4" on west face from which bears: SP stump 41" dia. N57°W 31' (RI) SP 24° N57°W 32.3' SP stump 72" dia. S46°E 26.9' (RI) SP 54° S40E 24.4' Established new BT's which bear from corner stone: WF 4" DBH N 4° E 9.2' Scribed X BT, Tagged LS3848 WF 5" DBH S 57°E 4.6' Scribed X BT, Tagged LS 3848	N 1/16 34 35	SET 1"x48" IP 36" in ground with 1 1/2" Brass Cap marked: T23N RII E Raised rock mound 30" diameter by 14" high from which bears: WF 11" DBH S61°W 1.8' Scribed 1/16 BT, Tagged LS 3848 S34 S35 1974 WF 12" DBH S 6° W 28.3' Scribed 1/16 BT, Tagged LS 3848 LS 3848 1/2" Rebar with yellow plastic cap stamped RCE III 173 bear S26°10'04"E 23.22' (R/S 4-17)
1/4 2 11	Found corner stone 10"x10"x5" (14"x12"x5" diagonally) marked 1/4" (RI) 14"x12"x5". Also Found original BT. Re-established corner at location of corner stone and N15°W 19.8' from scribed face of BT SET 1"x36" IP 26" in ground with 1 1/2" Brass Cap marked: T22N RII E Raise rock mound 36" diameter by 12" high from which bears: WF 17" DBH N 41° E 13.6' Scribed 1/4 S2 BT, Tagged LS3848 S2 S11 1974 WF 17" DBH S 76°W 16.9' Scribed 1/4 S11 BT, Tagged LS3848 LS 3848 PP 49" DBH S 15° E 21.5' Scribed 1/4 S BT, Tagged LS3848 (RI) PP 50" dia S15°E 19.8'	1/4 33 34 4 3	Found 4"x11"x16" corner stone in rock mound with 3 notches on east and 3 notches on west, (RI) 4x11x16, from which bears: SP stump 54" dia. N35°E 72.9' (RI) Pitch pine 40" N35°E 71.3' SET 1"x48" IP 41" in ground at corner stone location with 1 1/2" Brass Cap marked: T23N RII E Rebuilt rock mound 24" diameter by 12" high from which 1/4 S27 established new BT's bear: S33 S34 SP 12" DBH S69°E 8.8' Scribed S3 BT, Tagged LS3848 S4 S3 T22N WF 10" DBH N89°E 16.9' Scribed S34 BT, Tagged LS3848 1974 LS 3848 WF 8" DBH S89°W 27.8' Scribed S4 BT, Tagged LS3848 WF 9" DBH N74°W 62.6' Scribed S33 BT, Tagged LS3848	E 1/16 S34	SET 1"x48" IP 36" in ground with 1 1/2" Brass Cap marked: T23N RII E Raised rock mound 44" diameter by 15" high from which bears: WF 4" DBH S58°E 13.3' Scribed 1/16 BT, Tagged LS 3848 S34 S35 WF 4" DBH S75°W 7.9' Scribed 1/16 BT, Tagged LS 3848 LS 3848
1/4 3 2	Found corner stone 10"x10"x5" (14"x12"x5" diagonally) marked 1/4" (RI) 14"x12"x5". Also Found original BT. Re-established corner at location of corner stone and N15°W 19.8' from scribed face of BT SET 1"x36" IP 26" in ground with 1 1/2" Brass Cap marked: T22N RII E Raise rock mound 36" diameter by 12" high from which bears: WF 17" DBH N 41° E 13.6' Scribed 1/4 S2 BT, Tagged LS3848 S2 S11 1974 WF 17" DBH S 76°W 16.9' Scribed 1/4 S11 BT, Tagged LS3848 LS 3848 PP 49" DBH S 15° E 21.5' Scribed 1/4 S BT, Tagged LS3848 (RI) PP 50" dia S15°E 19.8'	1/4 34 3 3	Found no evidence of original, Re-established by single proportion. SET 1"x48" IP 36" in ground with 1 1/2" Brass Cap marked: T23N RII E Raised rock mound 36" diameter by 12" high from which bears: 1/4 S34 IC 14" DBH S 4° W 84.7' Scribed S3 1/4 BT, Tagged LS3848 S3 T22N IC 18" DBH N 54° E 72.0' Scribed S34 1/4 BT, Tagged LS3848 1974 LS 3848	S 1/16 S34	SET 1"x36" IP 24" in ground with 1 1/2" Brass Cap marked: LS 3848 Raised rock mound 36" diameter by 12" high from which bears: DF 7" DBH S 11°W 10.2' Scribed 1/16 BT, Tagged LS 3848 S34 SE 1/16 SP 12" DBH S 62° E 44.3' Scribed 1/16 BT, Tagged LS 3848 1974
34 35 3 2	Found stone 23"x12"x4" with possible 1/4 on West side in recent stone mound, (RI) 15"x12"x8". Old K-Tag, ± 1930, imbedded in cedar snag next to mound. SET 1"x48" IP 38" in ground with 1 1/2" Brass Cap marked: T22N RII E Raised rock mound 36" diameter by 15" high from which bears: WF 7" DBH N88°E 26.8' Scribed S2 1/4 BT, Tagged LS3848 S3 S2 1974 WF 18" DBH N43°W 12.9' Scribed S3 1/4 BT, Tagged LS3848 LS 3848 DF 50" DBH N41°E 18.0' Bark Scribed V4S BT (RI) Spruce 40" dia N10°E 13.9' WF Snag 26" DBH S88°W 47.0' Scribed 1/4 S BT (RI) Fir 12" dia N85W 46.2'	1/4 4 3	Found no evidence of original, Re-established by single proportion. SET 1"x36" IP 21" in ground with 1 1/2" Brass Cap marked: T22N RII E Raised rock mound 36" diameter by 12" high from which bears: 1/4 S34 IC 14" DBH S 4° W 84.7' Scribed S3 1/4 BT, Tagged LS3848 S3 SP 13" DBH S50°W 27.6' Scribed S4 1/4 BT, Tagged LS3848 1974 LS 3848 SP 14" DBH S75°E 10.9' Scribed S3 1/4 BT, Tagged LS 3848	ABBREVIATIONS:	IP = Iron Pipe, galvanized where set this survey. BT = Bearing Tree DBH = Diameter Breast High, 4.5' above high ground level. PP = Ponderosa Pine SP = Sugar Pine WF = White Fir DF = Douglas Fir IC = Incense Cedar RF = Red Fir
27 26 34 35	Found 1/2" rebar with yellow plastic cap marked RCE III 173 in 48" diameter x 12" high rock mound from which bears: WF 21" DBH (almost dead) N 28°E 14.9' (RI) Fir 14" N34°E 14.5' Stump hole S19°E 25.7' (RI) Fir 16" S22°E 25.7' Stump hole S35°W 63.0' (RI) Fir 16" S42°W 58.1' Established new BT's which bear from rebar: DF 10" DBH S28°W 9.6' Scribed S3 BT, Tagged LS3848 SP 11" DBH S11°E 15.6' Scribed S2 BT, Tagged LS 3848 WF 7" DBH N48°E 15.5' Scribed S35 BT, Tagged LS3848 DF 12" DBH N16°W 28.6' Scribed S34 BT, Tagged LS3848	4 3 9 10	Found corner stone 17"x8"x11", (RI) 13x12x10, with 3 notches on east edge and 5 scratches on south face, stone mound on east side of corner stone. Original BT's bear from corner stone: RF 38" DBH S 72°W 21.5' (RI) Fir 36" S86°W 20.5' RF 36" DBH N41°W 21.1' (RI) Fir 36" N40°W 19.8' RF 26" DBH N80°E 69.4' (RI) Fir 24" N80°E 68.6' SP 36" DBH S36°E 13.2' tree opened-scribed, Tagged LS3848, (RI) Fir 40" S15°E 9.9' 1" IP S 12°E 2.3' SET 1"x36" IP 30" in ground, at corner stone location, with 1 1/2" Brass Cap marked: T22N RII E 4 3 9 10 1974 LS 3848 Rebuilt rock mound around Brass Cap, reset corner stone next to Brass Cap, mound 4'x3'x15" high.		
1/4 34 35	Found recent rock mound in old road with 13"x8"x7", (RI) 14x8x7, with recently chiseled "X" in top, 1 notch on south, 2 notches on east, 48" diameter by 15" high rock mound, from "X" bears: PP 29" DBH N 7° W 15.4' (RI) Pine 10" N52°W 14.5' SP 55" DBH N46°E 44.1' faint scribing (RI) SP 42" N45 3/4°E 41.6' PP 46" DBH S 56°E 37', down (RI) Pine 42" S55 1/4°E 35.6' DF stump 52" S60°W 65.3' (RI) Spruce 36" S59 3/4°W 64.0' Established new BT's which bear from "X"; DF 12" DBH N 40°E 25.0' Scribed S26 BT, Tagged LS 3848 DF 7" DBH S 10°W 20.3' Scribed S34 BT, Tagged LS 3848 IC 5" DBH S 41° E 15.7' Scribed S35 BT, Tagged LS 3848	1/4 34 35	Found no evidence of original corner, re-established by single proportion. SET 1"x48" IP 36" in ground with 1 1/2" Brass Cap marked: T23N RII E Raised rock mound 36" diameter by 12" high from which bears: 1/4 S34 DF 7" DBH S60°W 13.1' Scribed S34 1/4 BT, Tagged LS3848 1974 DF 6" DBH N35°E 21.2' Scribed S35 1/4 BT, Tagged LS3848 LS 3848 1/2" rebar with yellow plastic cap marked RCE III 173 (R/S 4-17) bears S36°20'19"E 12.72'		
1/4 3 10	No evidence of original corner, re-established by single proportion. SET 1"x48" IP 36" in ground with 1 1/2" Brass Cap marked: T22N RII E Raised rock mound 36" diameter by 12" high from which bears: 1/4 S3 SP 15" DBH N 5° E 8.2' (from face) Scribed 1/4 S3 BT 1974 WF 17" DBH S78°E 10.5' Scribed 1/4 S10BT, BT's tagged LS 3848	C 1/4 S3	SET 1"x48" IP 38" in ground with 1 1/2" Brass Cap marked: T22N RII E from which bears: C1/4 S3 WF 7" DBH S87°E 43.1' Scribed C1/4 BT 1974 LS3848 WF 8" DBH N47°W 20.3' Scribed C1/4 BT BT's tagged LS 3848		

## DESCRIPTION OF MONUMENTS

FEBRUARY 1975 JAMES F. NICKLOS LS 3848

## RECORD OF SURVEY

PORTION OF E/2 SECTION 34, T. 23 N., R. 11 E., &

NE/4, SECTION 3, T. 22 N., R. 11 E., M.D.B. & M.

UNINCORPORATED AREA OF PLUMAS COUNTY,

CALIFORNIA

SHEET 2 OF 2

4RS 83