


- 55) 1/4 Sections 29-32 Found Orig G.L.O. 42"x24"x24" corner stone. Found 3/4" iron bar with 2 1/2" disc L.S. 2061 N 28° 36' E 53.20' (5-RS-25). Set U.S.F.S. monument S 86° 45' E 5.0' of G.L.O. corner stone, as reference monument. Marked B.T's to reference monument 11" Fir S 27° W 10.8'; 16" Fir N 15° E 27.5'
- 56) CS 1/16 Section 32. Set U.S.F.S. monument in stone mound. Marked B.T's 11" Fir S 14° E 9.0'; 9" Fir S 82° W 14.9'
- 57) 1/4 Sections 32-5. Found 3/4" iron bar with 2 1/2" disc L.S. 2061 in stone mound. Found B.T's 20" Fir N 12° W 50.5'; 14" Fir S 33° E 36.9'
- 58) SW 1/16 Section 32. Set U.S.F.S. monument in stone mound. Marked B.T's 5" Fir N 5° W 18.7'; 6" Fir S 33° W 33.4'
- 59) Section corner $\frac{31}{6} \frac{32}{5}$ Found 3/4" iron bar with 2 1/2" disc L.S. 2061 in stone mound. Found B.T's 14" Fir S 9° W 5.3' 16" Fir S 61° W 14.5'
- 60) 1/4 Sections 31-32. Found 3/4" iron bar with 2 1/2" disc L.S. 2061 in stone mound. Found B.T's 8" Cedar N 89° E 13.3'; 13" Cedar S 82° W 6.6'
- 61) N 1/16 Sections 31-32. Found 3/4" iron bar with 2 1/2" disc L.S. 2061 in stone mound. No B.T's found.
- 62) W 1/16 Sections 32-29. Found 3/4" iron bar with 2 1/2" disc L.S. 2061 in stone mound. (Note corner not at proper position). Set U.S.F.S. monument in stone mound. S 29° 34' W 26.56' from L.S. 2061 monument. Marked B.T's 20" Fir S 45° E 31.6'; 15" Fir N 15° E 24.3'
- 63) Section corner $\frac{30}{31} \frac{29}{32}$ Found 1 1/2" Pipe with 2" screw on cap in stone mound. L.S. 2061. Found G.L.O. B.T's 48" Fir (down and rotting) N 43° W 29.7'; 55" Cedar N 48° E 35.6' 36" Pine (stump) S 76° E 22.4'; 24" Pine (stump) S 45° W 37.0' Set U.S.F.S. monument in stone mound, in place of L.S. 2061 monument, reset L.S. 2061 pipe next to new monument. Marked B.T's 14" Cedar S 12° W 29.4' 8" Cedar N 31° W 37.9'
- 64) S 1/16 Sections 30-29. Set U.S.F.S. monument in stone mound. Marked B.T's 30" Fir N 38° W 2.0'; 16" Fir S 81° E 35.0'
- 65) S W 1/16 Section 29. Set U.S.F.S. monument in stone mound. Marked B.T's 17" Fir N 66° W 35.0'; 16" Fir N 18° E 29.0'
- 66) C W 1/16 Section 29. Set U.S.F.S. monument in stone mound. Marked B.T's 16" Fir N 55° W 19.0'; 12" Fir South 2.1'
- 67) 1/4 Sections 30-29. Set U.S.F.S. monument in stone mound. Marked B.T's 4" Fir N 75° W 19.0'; 12" Fir N 26° E 3.8' Prorate Position.
- 68) Section corner $\frac{19}{30} \frac{20}{29}$ Found Orig G.L.O. B.T's Pine (snag) N 42° W 15.2'; Fir (snag) S 51° W 22.4'. Set U.S.F.S. monument in stone mound, record G.L.O. distances from B.T's. Marked B.T's 7" Fir N 41° W 23.0'; 8" Oak S 61° W 9.0' 6" Fir S 22° E 22.0'
- 69) 1/4 Sections 19-30. Found Orig G.L.O. 13"x10"x6" corner stone. Set U.S.F.S. monument in stone mound with G.L.O. corner stone buried along side. Marked B.T's 15" Pine N 84° E 20.3'; 10" Pine S 17° W 12.5'
- 70) Section corner $\frac{24}{19} \frac{30}{30}$ Found 1926 G.L.O. monument Found G.L.O. B.T's 79" Pine N 40° W 29.5'; 48" Fir N 36° E 38.5'; 14" Pine S 16° E 38.7'
- 71) CS-NE -NW 1/256 Section 30. Set U.S.F.S. monument in stone mound. Marked B.T's 13" Pine N 21° W 14.4' 12" Cedar N 85° E 22.5'
- 72) CS-CN-NW 1/256 Section 30. Set U.S.F.S. monument in stone mound. Marked B.T's 6" Oak N 11° E 11.1'; 7" Oak S 63° E 15.4'
- 73) NW 1/16 Section 30. Set U.S.F.S. monument in stone mound. Marked B.T's 9" Cedar S 73° W 11.8'; 6" Cedar N 13° W 24.0'
- 74) Section corner $\frac{24}{25} \frac{30}{30}$ Found 1926 G.L.O. monument. Found G.L.O. B.T's 22" Pine S 17° W 55.9'; 28" Oak N 88° W 34.0'; 18" Oak N 16° W 53.6'; 25" Oak N 8° W 33.0'
- 75) W 1/4 Section 30 only. Found Orig G.L.O. monument in stone mound. Found G.L.O. B.T's 6" Fir S 3° E 18.5' 15" Fir N 48° W 9.0'
- 76) CE-WC 1/64 Section 30. Set U.S.F.S. monument in stone mound. Marked B.T's 14" Fir S 18° W 6.8'; 6" Oak East 12.3'
- 77) E 1/4 Section 25 only. Found 1926 G.L.O. monument. Found G.L.O. B.T's 60" Pine S 37° W 20.1'; 14" Fir N 53° W 15.3'
- 78) Section corner $\frac{25}{31} \frac{30}{31}$ Found 1926 G.L.O. monument. Found G.L.O. B.T's 39" Fir N 44° E 17.2'; 32" Fir S 50° E 17.8' 14" Fir S 15° W 19.8'
- 79) 1/4 Sections 30-31. Found 3/4" iron bar with 2 1/2" disc L.S. 2061. Found G.L.O. B.T. 36" Pine (snag) N 83° E 56.1'. Found L.S. 2061 B.T's 23" Pine S 68° W 12.5'; 18" Fir N 19° E 8.2'
- 80) SE 1/16 Section 30. Set U.S.F.S. monument in stone mound. Marked B.T's 14" Fir S 75° E 12.4'; 7" Fir N 28° W 14.4'
- 81) E 1/16 Sections 30-31. Found 3/4" iron bar with 2 1/2" disc L.S. 2061 in stone mound. Found no B.T's.
- 82) NE 1/16 Section 31. Found 3/4" iron bar with 2 1/2" disc L.S. 2061. Found no B.T's.
- 83) CN 1/16 Section 31. Set U.S.F.S. monument in stone mound. Marked B.T's 12" Fir S 43° E 15.5'; 7" Cedar S 45° W 18.4'
- 84) NW 1/16 Section 31. Set U.S.F.S. monument in stone mound. Marked B.T's 8" Pine N 57° W 26.9'; 7" Fir N 19° E 30.0'
- 85) Section corner $\frac{25}{36} \frac{31}{31}$ Found 1926 G.L.O. monument in stone mound. Found G.L.O. B.T's 33" Fir S 53° W 19.1'; 16" Fir N 48° W 37.0'
- 86) W 1/4 Section 31 only. Found Orig G.L.O. corner stone with L.S. 2061 monument next to corner stone, in stone mound. Found G.L.O. B.T's 24" Fir S 38° E 42.2'; 12" Oak S 42° W 29.0'. Found L.S. 2061 B.T's 29" Fir S 83° E 12.1' 35" Fir S 43° W 8.1'
- 87) C W 1/16 Section 31. Set U.S.F.S. monument 6" under surface dirt road. Marked B.T's 4" Cedar N 48° W 62.4' 18" Cedar S 43° W 28.6'
- 88) CE 1/16 Section 31. Set U.S.F.S. monument in stone mound. Marked B.T's 9" Fir S 58° W 20.6'; 9" Fir S 29° E 18.8'
- 89) SE 1/16 Section 31. Set U.S.F.S. monument in stone mound. Marked B.T's 6" Fir N 17° W 4.1'; 4" Fir N 79° E 9.1'
- 90) CS 1/16 Section 31. Set U.S.F.S. monument in stone mound. Marked B.T's 13" Fir N 60° E 5.6'; 20" Cedar N 61° W 7.8'
- 91) S W 1/16 Section 31. Set U.S.F.S. monument in stone mound. Marked B.T's 11" Fir N 39° W 13.3'; 9" Fir N 30° E 25.0'
- 92) 1/4 Section 36 only. Found 1926 G.L.O. monument in stone mound. Found B.T. 16" Fir S 47° E 19.1'
- 93) Section corner $\frac{36}{6} \frac{31}{6}$ Found 1926 G.L.O. monument in stone mound. Found B.T's 34" (snag) N 7° E 120.1'; 19" Fir N 88° E 104.9'
- 94) 1/4 Sections 31-6. Found 3/4" iron bar with 2 1/2" disc L.S. 2061. Found B.T's 16" Fir N 12° W 30.8'; 18" Fir S 14° W 38.4'



RECORD OF SURVEY
 FOR LOUISIANA PACIFIC CORP. & THE PLUMAS
 NATIONAL FOREST OF SECTIONS 26 THRU 34
 T. 22 N., R. 8 E., M.D.M. COUNTY OF PLUMAS, CA.
 DAWSON - BURGESS LAND SURVEYS REDDING, CALIFORNIA
 FALL 1980 SHEET 4 OF 4 SHEETS