


① PROPERTY CORNER #1 (NE CORNER OF SOUTHERLY B CHAINS OF THE NE 1/4 OF THE SE 1/4 SECTION 23)


SET: 5/8" DRIVE-IN ALUMINUM ROD 24" LONG W/ 3/4" ALUMINUM CAP MARKED



FROM WHICH: 18" W. FIR BEARS S82 1/2° W 8.3 FT. MARKED W/ "X" AT BREAST HEIGHT AND "BT" AT ROOT CROWN.

② PROPERTY CORNER #2 (NW CORNER OF SOUTHERLY B CHAINS OF THE NE 1/4 OF THE SE 1/4 SECTION 23)

SET: 5/8" DRIVE-IN ALUMINUM ROD 60" LONG W/ 3/4" ALUMINUM CAP MARKED



IN 6" x 18" MOUND OF ROCKS

FROM WHICH: 12 1/2" D. FIR BEARS S24° E 48.2 FT. MARKED W/ "X" AT BREAST HEIGHT AND "BT" AT ROOT CROWN.

③ 14 | 13 / 23 | 24 FOUND: STANDARD 2 1/2" BLM BRASS CAP MONUMENT IN STONE MOUND PER 6 R.S. 82 (1970)

FROM WHICH: 54" D. FIR BRS. N63° E 71 LKS. (37" SPRUCE BRS. N63° E 71 LKS. ; 6LD) 9" FIR BRS. N51° W 39 LKS. 10" B. OAK BRS. S41° E 36 LKS. 7" FIR BRS. S69° W 17 LKS.

④ 1/4 | 6/14 / 5/23 FOUND: STANDARD 2 1/2" BLM BRASS CAP MONUMENT IN STONE MOUND PER 6 R.S. 82 (1970)

FROM WHICH: 31" P. PINE BRS. N11° E 98 LKS. (12" P. PINE BRS. N11° E 98 LKS. ; 6LD) 6" W. FIR BRS. N50° E 37.5 LKS. 8" P. PINE BRS. S21° E 98 LKS.

⑤ 1/4 / 5/22 | 5/23 FOUND: STANDARD 2 1/2" USFS ALUMINUM MONUMENT IN STONE MOUND PER 6 R.S. 14 (1960)

FROM WHICH: 27" CEDAR BRS. S83° W 19.4 FT.

⑥ 27 | 23 / 27 | 26 FOUND: STANDARD 2 1/2" BLM BRASS CAP MONUMENT IN STONE MOUND PER 6 R.S. 14 (1970)

FROM WHICH: 14" D. FIR BRS. N41° E 22.1 FT. 20" D. FIR BRS. S55° E 12.5 FT. 10" CEDAR BRS. S04° W 33.0 FT. 18" D. FIR BRS. N72° W 34.3 FT.

⑦ 1/4 | 6/23 / 5/26 FOUND: STANDARD 2 1/2" BLM BRASS CAP MONUMENT (1970)

FROM WHICH: FIR STUMP W/ SCRIBING BRS. N33 1/2° E 74.0 FT. (25" FIR BRS. N33 1/2° E 109 LKS. ; 6LD) 37" FIR W/ SCRIBING BRS. S20° W 28.3 FT. (10" FIR BRS. S20 1/2° W 43 LKS. ; 6LD) 10" FIR W/ HEALED BLAZE BRS. N66° E 20.5 FT. (FIR BRS. N67° E 31 LKS. ; 1970 BLM) 12" FIR W/ HEALED BLAZE BRS. S05 3/4° W 18.5 FT. (FIR BRS. S07° W 28 LKS. ; 1970 BLM)

⑧ 23 | 24 / 26 | 25 FOUND: STANDARD 2 1/2" BLM BRASS CAP MONUMENT (1970)

FROM WHICH: 45" P. PINE W/ SCRIBING BRS. S60 3/4° W 300.3 FT. (30" P. PINE BRS. S60° W 458 LKS. ; 6LD) 26" FIR W/ HEALED BLAZE BRS. S66 3/4° W 225.4 FT. (FIR BRS. S67° W 343 LKS. ; 1970 BLM) 16 1/2" P. PINE W/ HEALED BLAZE BRS. N65 1/4° W 201.3 FT. (P. PINE BRS. N66° W 306 LKS. ; 1970 BLM)


⑨ 1/4 | 6/24 / 5/25 FOUND: STANDARD 2 1/2" BLM BRASS CAP MONUMENT (1970) FROM WHICH: 20" CEDAR SNAG W/ SCRIBING BRS. N17° E 49.2 FT. (22" CEDAR BRS. N16 1/2° E 73 LKS. ; 6LD) 28 1/2" CEDAR W/ HEALED BLAZE BRS. S55 1/4° W 6.8 FT. (20" CEDAR BRS. S64° W 10 LKS. ; 6LD) 10" FIR W/ HEALED BLAZE BRS. N15 3/4° W 49.3 FT. (FIR BRS. N17° W 45 LKS. ; 1970 BLM)

⑩ 1/4 / 5/24 | 6/19 | 6/19 FOUND: STANDARD 2 1/2" BLM BRASS CAP MONUMENT (1970) FROM WHICH: 20" CEDAR SNAG W/ SCRIBING BRS. N31 1/2° E 70.1 FT. (20" CEDAR BRS. N33 1/2° E 105 LKS. ; 6LD) 22" P. PINE W/ SCRIBING BRS. S72 1/4° W 64.3 FT. (12" P. PINE BRS. S73° W 96 LKS. ; 6LD) 7" CEDAR W/ HEALED BLAZE BRS. S39 3/4° E 39.5 FT. (CEDAR BRS. S33° E 60 LKS. ; 1970 BLM) 8" P. PINE W/ HEALED BLAZE BRS. N23 1/4° W 27.6 FT. (PINE BRS. N17° W 41 LKS. ; 1970 BLM)

⑪ 1/4 | 6/13 / 5/24 FOUND: STANDARD 2 1/2" BLM BRASS CAP MONUMENT (1970) FROM WHICH: 8" CEDAR W/ HEALED BLAZE BRS. N32° E 27.7 FT. (CEDAR BRS. N33 1/2° E 42 LKS. ; 1970 BLM) 5" CEDAR W/ HEALED BLAZE BRS. S38 3/4° E 24.2 FT. (CEDAR BRS. S37° E 37 LKS. ; 1970 BLM) 27" P. PINE W/ SCRIBING BRS. S04 3/4° W 51.5 FT. (20" P. PINE BRS. S04 3/4° W 77 LKS. ; 6LD) 25" P. PINE W/ SCRIBING BRS. N33 1/2° W 50.3 FT. (20" P. PINE BRS. N32 1/2° W 75 LKS. ; 6LD)


⑫ 1/4 / 5/23 | 5/24 FOUND: NO EVIDENCE OF CORNER MONUMENT OR ACCESSORIES RECORD: SET POST FROM WHICH BEARS: 52" P. PINE S66° E 117 LKS. 32" P. PINE S59 1/2° W 240 LKS.

SET: STANDARD USFS MONUMENT FOR WITNESS CORNER S00° 33' 15" E 35.90 FT. FROM SINGLE-PROKATE POSITION WHICH FALLS IN AN IRRIGATION DITCH MKD. FROM WHICH: 23" P. PINE BRS. S84° E 20.6 FT. MARKED W/ "X" AT BREAST HT. AND "BT" AT ROOT CROWN 28" FIR BRS. N74 3/4° W 8.2 FT. MARKED W/ "X" AT BREAST HT. AND "BT" AT ROOT CROWN




⑬ 6 | 1/16 / 5/22 | 5/23 FOUND: STANDARD 2 1/2" USFS ALUMINUM CAP MONUMENT FOR WITNESS CORNER (S00° 37' 00" E 65.0 FT.) PER 6 R.S. 14 FROM WHICH: 39" P. PINE BRS. S64° E 51.4 FT. 6" P. PINE BRS. S45° W 41.7 FT. 5" P. PINE BRS. S85 1/2° W 17.1 FT. NOTE: BT'S SCRIBED "X" AT BREAST HT. "BT" AT ROOT CROWN


⑭ CN | 1/16 / 5/23 SET: 5/8" DRIVE-IN ALUMINUM ROD 24" LONG W/ 3/4" ALUMINUM CAP MARKED 6" BELOW GROUND IN GRAVELLED DRIVEWAY FROM WHICH: 17 1/2" P. PINE BRS. N44 1/4° E 61.6 FT. MARKED "CN 1/16 523 BT" 16 1/2" P. PINE BRS. N76 1/2° E 80.9 FT. MARKED "CN 1/16 523 BT"




⑮ SW | 1/16 / 5/23 SET: STANDARD USFS MONUMENT MARKED FROM WHICH: 10" FIR BRS. S38° E 55.0 FT. MARKED "SW 1/16 523 BT" 7 1/2" FIR BRS. S7 1/2° W 30.6 FT. MARKED "SW 1/16 523 BT"




⑯ CS | 1/16 / 5/23 SET: STANDARD USFS MONUMENT MARKED FROM WHICH: 11" FIR BRS. S36 1/2° E 13.6 FT. MARKED "CS 1/16 523 BT" 8" FIR BRS. S15° W 21.7 FT. MARKED "CS 1/16 523 BT" 2" D. D. IRON PIPE EXTENDING 31" ABOVE GROUND BRS. N62 1/2° W 8.1 FT.



⑰ SE | 1/16 / 5/23 SET: STANDARD USFS MONUMENT MARKED FROM WHICH: 13 1/2" FIR BRS. N15 1/2° E 21.1 FT. MARKED "SE 1/16 523 BT" 13" FIR BRS. S42° W 12.9 FT. MARKED "SE 1/16 523 BT"




⑱ N | 1/16 / 5/23 | 5/24 SET: STANDARD USFS MONUMENT MARKED FROM WHICH: 19" CEDAR BRS. N12 1/2° E 28.0 FT. MARKED "N 1/16 524 BT" 4 1/2" FIR BRS. N46 3/4° W 48.2 FT. MARKED "N 1/16 523 BT"




⑲ S | 1/16 / 5/23 SET: STANDARD USFS MONUMENT MARKED FROM WHICH: 10 1/2" P. PINE BRS. N66° W 39.6 FT. MARKED "S 1/16 523 BT"




⑳ W | 1/16 / 5/23 | 5/26 SET: STANDARD USFS MONUMENT MARKED FROM WHICH: 16" FIR BRS. S07 1/2° E 9.4 FT. MARKED "W 1/16 526 BT" 12" FIR BRS. N05 1/2° W 46.5 FT. MARKED "W 1/16 523 BT"




㉑ CW | NW | 1/16 / 5/24 SET: STANDARD USFS MONUMENT MARKED FROM WHICH: 15" P. PINE BRS. N48 1/2° E 10.7 FT. MARKED "CWNW 1/16 524 BT" 18" P. PINE BRS. N33 1/2° W 25.4 FT. MARKED "CWNW 1/16 524 BT"



㉒ CWW | 1/16 / 5/24 SET: 5/8" DRIVE-IN ALUMINUM ROD 48" LONG W/ 3/4" ALUMINUM CAP MARKED NO BT'S



㉓ CWSW | 1/16 / 5/24 SET: 5/8" DRIVE-IN ALUMINUM ROD 36" LONG W/ 3/4" ALUMINUM CAP MARKED FROM WHICH: 20" P. PINE BRS. S09 3/4° E 13.0 FT. MARKED "CWSW 1/16 524 BT" 18" P. PINE BRS. S55 3/4° W 35.0 FT. MARKED "CWSW 1/16 524 BT"



RECORD OF SURVEY SECTION 23 & 24, T.24N, R.8E, M.D.M.