

- CORNER NOTES -

- ① SEC. COR. 25, 26, 35 & 36 - Set a 2" Pipe w/3" B.C. in mound of rocks mkd. L.S. 3318 from Fd. Orig. B.T.'s (G.L.O. 1877):
1.) 36" P. Pine N. 53°W. 78.1 ft. (3" P. Pine N. 53 1/2°W. 123 lks.)
2.) 50" Fir w/blaze S. 73°W. 50.2 ft. (30" Fir S. 71 1/2°W. 77 lks.)
3.) 52" Fir S. 5°E. 76.8 ft. (30" Fir S. 5 1/4°E. 108 lks.)
Fd. B.T.:
1.) 15" Fir N. 88°E. 55.7 ft.
- ② N. 1/16 35/36 - Set 5/8" Rebar w/1 1/2" Alum. Cap in rock mound mkd. L.S. 3318 on a line from a fd. 61" P. Pine Line tree (See note 3) and by proportionate measure to ① above.
Scribed & tagged new B.T.'s:
1.) 12" Pine N. 46°E. 30.2 ft.
2.) 9" Fir S. 80°W. 10.0 ft.
- ③ Fd. 61" P. Pine Line Tree w/U.S.F.S. Location Poster attached. (54" Y. Pine - G.L.O. 1877)
- ④ 1/4 Cor. 35/36 - Fd. Rock Mound w/Stone mkd. 1/4 on W. face - Set a 2" I.P. w/3" B.C. mkd. L.S. 3318 in its place, and planted Stone upside down and alongside -
Scribed & tagged new B.T.'s:
1.) 9" Fir N. 75°E. 4.2 ft.
2.) 10" Cedar S. 39°W. 47.4 ft.
- ⑤ Fd. 48" S. Pine Line Tree (30" S. Pine - G.L.O. 1877).
- ⑥ SEC. COR. 35, 36, 1 & 2 - Set 2" I.P. w/3" B.C. mkd. L.S. 3318 from Orig. B.T. (G.L.O. - 1877):
1.) 36" Fir w/scar N. 55°W. 143.0 ft. (219 lks.)
Scribed & tagged new B.T.'s:
1.) 12" Fir N. 41°E. 9.4 ft.
2.) 12" Fir S. 53°E. 14.6 ft.
3.) 14" Fir S. 52°W. 17.5 ft.
- ⑦ SEC. COR. 30/31 - Fd. 2" Alum. Pipe w/3" Alum. Cap mkd. U.S.F.S., L.S. 3621 per 4 R.S. 148, Plumas County Records.
Fd. 10" W. Fir N. 67°E. 13.2 ft. per record.
- ⑧ SEC. COR. CC 25/36 - Set 2" I.P. w/3" B.C. in mound of rock mkd. L.S. 3318 from Fd. Orig. B.T. (G.L.O. - 1877):
1.) 26" P. Pine S. 81°W. 112.9 ft. (26" P. Pine S. 81°W. 171 lks.)
Scribed & tagged new B.T.'s:
1.) 10" Pine N. 30°W. 14.0 ft.
2.) 16" Pine S. 66°W. 31.0 ft.
- ⑨ LOT COR. S. 36 Lot 1/2 S. 31 - Set 5/8" Rebar w/1 1/2" Alum. Cap in rock mound mkd. L.S. 3318 at proportionate distance -
Scribed & tagged new B.T.'s:
1.) 20" Fir N. 76°W. 15.0 ft.
2.) 10" Fir S. 58°W. 25.0 ft.
- ⑩ W. 1/4 COR. SEC. 31 - Fd. 2" I.P. w/3" B.C. mkd. L.S. 3621 per 4, R.S. 148, P.C.R.
Record B.T.'s. Fd:
1.) 7" S. Pine S. 68°W. 27.0 ft.
2.) 13" Cedar S. 69°E. 25.2 ft.
3.) 9" Cedar S. 5°E. 20.7 ft.
- ⑪ SEC. COR. 36/31 - Fd. 1" Pipe mkd. L.S. 3202 between two Fir Trees per 4 R.S. 148, P.C.R. Also fd. 2" I.P. w/B.C. mon. for W.C. North 4.0 ft.
Record B.T.'s. Fd. (4 R.S. 148):
1.) 24" W. Fir N. 15°E. 26.1 ft.
2.) 24" R. Fir S. 35°E. 15.2 ft.
3.) 22" Y. Pine N. 70°W. 75.2 ft.
4.) 22" R. Fir S. 40°W. 13.2 ft.

- ⑫ SEC. COR. 36/1 - Set 2" I.P. w/3" B.C. 1.3' out of ground and in mound of stone per Manual mkd. L.S. 3318. Pipe is set on the produced line intersection through the fd. marked stone as shown in Detail "B", Sheet 2, and the re-established S.W. Cor. of Section 36 with the true west line of Section C.
Scribed & tagged new B.T.'s:
1.) 14" Fir N. 25°W. 43.0 ft.
2.) 10" Fir S. 65°W. 28.7 ft.
- ⑬ 1/4 COR. 1/6 - Fd. Old Rock Mound and blazed tree N. 5°W. 18.0 ft. - Set 2" I.P. w/3" B.C. in center of mound mkd. L.S. 3318 -
Scribed & tagged new B.T.'s:
1.) 42" Fir N. 20°E. 70.0 ft.
2.) 20" Fir N. 50°W. 24.0 ft.
Left Old Blazed Tree - 48" Fir - N. 5°W. 18.0 ft. as-is.
- ⑭ SEC. COR. 1, 6, 7 & 12 - Fd. 2" I.P. w/3" B.C. - B.L.M. 1975 -
Fd. B.T.'s:
1.) 5" Tamarack N. 30°E. 47.5 ft.
2.) 24" Tamarack S. 64°W. 70.0 ft.
3.) 12" Tamarack N. 8°W. 38.9 ft.
- ⑮ SEC. COR. 29, 30, 31, 32 - Fd. 2" I.P. w/3" B.C. - B.L.M. 1970 -
Fd. B.T.'s. (B.L.M. 1970)
1.) 10" Pine S. 33°E. 9.9 ft. (7" Pine S. 33°E. 15 lks.)
2.) 10" W. Fir S. 56°W. 22.4 ft. (6" W. Fir S. 56°W. 34 lks.)
- ⑯ N. 1/16 SEC. 31/32 - Set 5/8" Rebar w/1 1/2" Alum. Cap in mound of rocks mkd. L.S. 3318 - a fd. Rebar & Cap mkd. L.S. 3621 per 4 R/S 148 bears N. 79°45'E. 57.4 ft.
Scribed & tagged new B.T.'s:
1.) 12" Cedar S. 74°E. 30.6 ft.
2.) 12" Fir N. 50°W. 21.9 ft.
- ⑰ 1/4 COR. 31/32 Fd. 2" Alum. Pipe w/3" Alum. Cap mkd. U.S.F.S. - L.S. 3621 per 4 R.S. 148, P.C.R.
Fd. Record B.T.'s:
1.) 8" Fir N. 70°E. 47.8 ft. (5" W. Fir N. 70°E. 47.8 ft.)
2.) 5" Fir S. 47°W. 34.3 ft. (5" W. Fir S. 47°W. 34.3 ft.)
- ⑱ SEC. COR. 31, 32, 5 & 6 - Fd. 2" I.P. w/3" B.C. - B.L.M. 1970 - in mound of rocks. Fd. B.T.'s. (B.L.M. - 1970):
1.) Rotted & down 6" Fir - scribing visible - N. 57°E. 16.7 ft. to Stump Hole (6" W. Fir N. 55°E. 26 lks.)
2.) 15" Fir - scribing visible - N. 14°W. 37.8 ft. (15" W. Fir N. 14°W. 58 lks.)
- ⑲ 1/4 COR. 29/32 - Fd. 2" I.P. w/3" B.C. - B.L.M. Ref. Mon. bears N. 45°E. 12.0 ft. from 27" Pine Cor.
Fd. B.T.'s (B.L.M. 1970):
1.) 14" Cedar S. 77°E. 26.4 ft. (10" Cedar S. 77°E. 40 lks.)
2.) 8" Cedar N. 2°E. 40.9 ft. (4" Cedar N. 2°E. 62 lks.)
- ⑳ CN 1/16 SEC. 32 - Set 5/8" Rebar w/1 1/2" Alum. Cap in mound of rocks mkd. L.S. 3318.
Scribed & tagged new B.T.'s:
1.) 8" Fir N. 84°E. 37.7 ft.
2.) 12" Fir South 2.2 ft.
- ㉑ CS 1/16 SEC. 32 - Set 5/8" Rebar w/1 1/2" Alum. Cap in mound of rocks mkd. L.S. 3318 -
Scribed & tagged new B.T.'s:
1.) 8" Fir N. 57°W. 15.4 ft.
2.) 18" Fir S. 40°W. 26.1 ft.
- ㉒ 1/4 COR. 32/5 - Fd. 2" I.P. w/3" B.C. - B.L.M. 1970 - in mound of rocks -
Fd. B.T.'s (B.L.M. 1970):
1.) 8" W. Fir S. 31°E. 23.1 ft. (4" W. Fir S. 31°E. 35 lks.)
2.) 10" W. Fir N. 45°W. 19.1 ft. (8" W. Fir N. 45°W. 29 lks.)

- ㉓ 1/4 COR. 32/33 - Fd. 48" S. Pine Cor. & 2" I.P. w/3" B.C. - B.L.M. 1970 Ref. Mon. Bearing S. 48°W. 15.0 ft. from Cor.
Fd. B.T.'s. (B.L.M. 1970):
1.) 47" W. Fir S. 20°E. 18.5 ft. (41" Fir S. 20°E. 27 lks.)
2.) 18" W. Fir N. 76°W. 18.5 ft. (11" Fir N. 76°W. 27 lks.)
- ㉔ S. 1/16 32/33 - Calc. Int-x Point - L.S. 3621 Rod & Cap per 4 R.S. 149, P.C.R. not found. Set Temp. Point for line marking & posting at proportionate distance between points ㉓ & ㉕
- ㉕ SEC. COR. 32, 33, 4 & 5 - Fd. 2" I.P. w/3" B.C. - B.L.M. 1970 -
Fd. B.T.'s (B.L.M. 1970):
1.) 24" S. Pine S. 60°W. 27.7 ft. (20" S. Pine S. 60°W. 42 lks.)
2.) 22" R. Fir N. 55°E. 14.5 ft. (18" R. Fir N. 55°E. 22 lks.)
Other found. B.T.'s. in place.

SURVEYOR'S CERTIFICATE ~

This map correctly represents a survey made by me or under my direction in conformance with the requirements of the Land Surveyor's Act at the request of U.S.D.A. - Forest Service in Sept. - Oct., 1981.

Gerald H. Griffith
GERALD H. GRIFFITH ~ L.S. 3318
LICENSED LAND SURVEYOR
GERALD H. GRIFFITH
L.S. 3318
STATE OF CALIFORNIA

COUNTY SURVEYOR'S CERTIFICATE ~

This map has been examined for conformance with the requirements of the Land Surveyor's Act this 15th day of March, 1982.

Lawrence J. Brock
Lawrence J. Brock RCE 13528
Plumas County Surveyor

COUNTY RECORDER'S CERTIFICATE ~

Filed this 15th day of March, 1982, at 2:27 p.m. in Book 6 of Record of Surveys at Page 48, Plumas County Records, at the request of the County Engineer.

Ila Diqqs
County Recorder
Fee \$ 7.00
File No. 6956
By: Isabella Andrews
Deputy

"DAYS/FLAT/FORK CADASTRAL SURVEY"

RECORD OF SURVEY
FOR U.S.D.A. - FOREST SERVICE
LASSEN NATIONAL FOREST

IN
SEC. 36, T. 27N, R. 5E & SEC. 32, T. 27N, R. 6E, M.D.M., IN THE
COUNTY OF PLUMAS, STATE OF CALIFORNIA
SCALE 1" = 1000' December, 1981