


**CORNER NOTES**

- ① NE 1/16 Set: a std. USFS monument in stone mound, from which brs. a 33" P.P. S 82° 29' E 49.6 ft. scribed "NE 1/16 S14 BT"; a 26 1/2" P.P. S 14° 48' E 35.6 ft. scribed "NE 1/16 S14 BT".
- ② N 1/16 14/13 Set: a std. USFS monument in stone mound, from which brs. a 14" P.P. S 87° 07' E 56.4 ft. scribed "N 1/16 S13 BT"; a 13" P.P. S 37° 19' W 63.8 ft. scribed "N 1/16 S14 BT".
- ③ 11/12 14/13 Fd: a std. 2 1/2" BLM brass cap monument in stone mound, from which brs. a 5" I.C. N 19° E 29 lks.; a 6" I.C. S 19° E 21 lks.; a 7" P.P. S 36° W 51 lks.; a 7" P.P. N 62° W 51 lks.; as per official BLM record.
- ④ CE 1/16 Set: a std. USFS monument in stone mound, from which brs. a 12" P.P. N 30° 37' E 17.8 ft. scribed "CE 1/16 S14 BT"; a 23" P.P. S 53° 36' E 72.6 ft. scribed "CE 1/16 S14 BT".
- ⑤ 14/13 Fd: a std. 2 1/2" BLM brass cap monument in stone mound, from which brs. a 26" P.P. N 75° W 100 lks.; a 6" D.F. S 48° E 24 lks.; a 8" W.F. S 35° W 3 1/2 lks.; as per official record. (BLM)
- ⑥ 14/13 23/24 Fd: a std. 2 1/2" BLM brass cap monument in stone mound, from which brs. a 54" D.F. N 63° E 71 lks.; a 9" Fir N 51° W 39 lks.; a 10" B.O. S 41° E 36 lks.; a 7" Fir S 69° W 17 lks.; as per official BLM record.
- ⑦ SE 1/16 Set: a std. USFS monument in stone mound, from which brs. a 15" S.P. N 86° 02' E 59.3 ft. scribed "SE 1/16 S14 BT"; a 12" P.P. S 8° 27' W 38.9 ft. scribed "SE 1/16 S14 BT".
- ⑧ 1/4 14/23 Fd: a std. 2 1/2" BLM brass cap monument in stone mound, from which brs. a 31" P.P. N 11° E 98 lks.; a 6" W.F. N 50° E 37 1/2 lks.; a 8" P.P. S 21° E 98 lks.; as per official BLM record.
- ⑨ 15/14 22/23 Fd: a 3/4" I.P. w/ metal tag mkd. "RCE 13528" in stone mound. Replaced I.P. w/ a std. USFS monument in stone mound, from which brs. a 13 1/2" P.P. N 12° E 9.8 ft. scribed "T24NR8E S14 BT"; a 20" P.P. S 27° E 7.0 ft. scribed "T24NR8E S23 BT".
- ⑩ CS 1/16 Set: a std. USFS monument in stone mound, from which brs. a 16" P.P. N 67° 01' E 11.3 ft. scribed "CS 1/16 S14 BT"; a 13" D.F. N 36° 19' W 2.6 ft. scribed "CS 1/16 S14 BT".
- ⑪ 15/14 Fd: a 1/2" x 2" x 35" Iron Stake mkd. "S.R.CO." at a fence corner, from which brs. a 34" Pine Stump N 26 1/2° E 58 lks. (G.L.O. record: N 17 1/2° E 64 lks.); a 31" Pine Stump S 80° W 106 lks. (G.L.O. record: S 84° W 91 lks.). Replaced Iron Stake w/ a std. USFS monument in stone mound, from which brs. a 21" P.P. N 62° E 33.8 ft. scribed "1/4 S14 BT"; a 27 1/2" P.P. N 16 1/2° W 45.7 ft. scribed "1/4 S15 BT".
- ⑫ 10/11 15/14 Fd: a std. 2 1/2" BLM brass cap monument in stone mound, from which brs. a 8" P.P. N 53° E 27 lks.; a 10" W.F. S 67° E 39 lks.; a 10" W.F. S 49° W 18 lks.; a 9" P.P. N 42° W 66 lks.; as per official BLM record.
- ⑬ W 1/16 11/14 Set: a std. USFS monument in stone mound, from which brs. a 17" P.P. N 53° 35' W 13.8 ft. scribed "W 1/16 S11 BT"; a 17" P.P. S 71° 04' E 11.6 ft. scribed "W 1/16 S14 BT".
- ⑭ 1/4 11/14 Set: a std. USFS monument in stone mound, from which brs. a reference monument, a std. USFS monument in stone mound, N 0° 12' W 186.28 ft. mkd. as shown below:



NOTE: The std. USFS monument is a Bernsten A-1-BR Break-off Monument consisting of a 2" diameter aluminum pipe, 27 1/2" long, w/ a magnet in a 2 1/2" x 5" cast aluminum base designed to break off on impact if the monument is disturbed, and a 3 1/4" aluminum cap mkd. as per the Manual Of Instructions For The Survey Of The Public Lands Of The United States, 1973 for the respective corners.

NOTE: Details A, B, C, D, E, F are not to scale.