

CORNER NOTES

NOTE:

STANDARD UNITED STATES FOREST SERVICE SURVEY MONUMENTS SET IN THIS SURVEY ARE 2 1/2" ALUMINUM PIPES 30" LONG WITH A 3" CAP AND CAST FLANGED BREAK AWAY BASE, STAMPED WITH APPROPRIATE CORNER DESIGNATION, (AS PER MANUAL OF SURVEYING INSTRUCTIONS 1973), L.S. 5287, 1983 OR 1984.

CORNER

- 1 1/4 COR. SEC'S. 22 AND 23 (REC. 15"X8"X3" STONE IN STONE MOUND) FOUND A STONE MOUND AND 30" D. FIR N 43° 22' E 21.4' WITH OPEN BLAZE (REC. 12" FIR N 44° 12' E 32 LKS.) SET A U.S.F.S. S.S.M. IN A 24"X4" M.O.S. F.W.B. A 7" CEDAR S 54° E 29.8' MKD. 1/4 S 23 BT, AND A 15" W. FIR S 68° W 23.0' MKD. 1/4 S 22 BT.
2 1/4 COR. SEC'S. 23 AND 26, FOUND A STD. B.L.M. BRASS CAP MONUMENT IN A 30"X8" M.O.S. SET IN 1973, A 10" BLACK OAK S 47° 39' E 22.2' WITH CLOSED BLAZE, A 35" W. FIR N 17° 21' E 17.5' WITH OPEN BLAZE SCRIBING VISIBLE, MKD. A 20" CEDAR S 39° E 41.1' MKD. 1/4 S 26 BT, A 9" CEDAR N 42° 30' E 49.1' MKD. 1/4 S 23 BT.
3 SEC. COR. SEC'S. 22, 23, 26 AND 27, NO EVIDENCE FOUND, POSITION DETERMINED BY DOUBLE PROPORTIONATE MEASUREMENTS. SET A U.S.F.S. S.S.M. IN A 36"X14" M.O.S. F.W.B. A 11" D. FIR N 54° 40' E 43.4' MKD. T26 NR 9 E S 23 BT, A 15" D. FIR S 2° 58' E 22.7' MKD. T26 NR 9 E S 26 BT, A 5" D. FIR S 46° 08' W 16.3' MKD. T26 NR 9 E S 27 BT, A 28" CEDAR N 15° 58' W 51.5' MKD. T26 NR 9 E S 22 BT.
4 E 1/16 COR. SEC'S. 22 AND 27, SET A U.S.F.S. S.S.M. IN A 30"X8" M.O.S., F.W.B. A 15" D. FIR N 0° 40' E 30.2' MKD. E 1/16 S 22 BT, A 7" D. FIR S 9° 02' W 26.5' MKD. E 1/16 S 27 BT.
5 1/4 COR. SEC'S. 22 AND 27 (REC. 18"X6"X6" STONE IN M.O.S., 8" OAK S 58° 1/4 E 5 LKS.) FOUND 24"X12" M.O.S., ACCEPTED AS THE ORIGINAL CORNER FROM COLLATERAL EVIDENCE OF MEASUREMENTS TO OTHER FOUND CORNERS, SET A U.S.F.S. S.S.M. IN 30"X12" M.O.S., F.W.B. A 5" D. FIR N 2° E 24.9' MKD. 1/4 S 22 BT, A 16" W. FIR S 19° W 28.6' MKD. 1/4 S 27 BT.
6 SEC. COR. SEC'S 21, 22, 27 AND 28 FOUND A STD. B.L.M. BRASS CAP MONUMENT IN A 24"X8" M.O.S. SET IN 1973, A 18" FIR N 37° 21' E 27' WITH HEALED BLAZE, A 18" S. PINE N 63° 43' W 19.5' WITH HEALED BLAZE, A 10" FIR S 84° 04' W 20.5' WITH OPEN BLAZE SCRIBING VISIBLE.
7 N 1/16 COR. SEC'S. 27 AND 28, SET A U.S.F.S. S.S.M. IN A 24"X6" M.O.S., F.W.B. A 8" W. FIR N 39° W 12' MKD. N 1/16 S 25 BT, A 4" P. PINE S 71° 30' E 7.1' MKD. N 1/16 S 27 BT.
8 CN 1/16 COR. SEC. 27, SET A U.S.F.S. S.S.M. IN A 30"X12" M.O.S., F.W.B. A 15" CEDAR S 35° 36' W 16.8' MKD. CN 1/16 S 27 BT, A 10" W. FIR N 62° 39' W 19.6' MKD. CN 1/16 S 27 BT.
9 1/4 COR. SEC'S 26 AND 35 (REC. 24"X16"X14" QUARTZITE STONE) FOUND NO EVIDENCE OF COR. STONE. FOUND 27" P. PINE WITH OPEN BLAZE AND 3 BT VISIBLE ON SOUTHEAST SIDE (REC. 24" SPRUCE N 35° W 70 LKS). REVERSAL OF SPECIES IN ORIGINAL FIELD NOTES VERIFIED BY CABIN SITE AND TOPOGRAPHY CALLS AS REPORTED BY A. W. KEDDIE AND RING COUNT OF BLAZE TO DATE OF ORIGINAL SURVEY. SET U.S.F.S. S.S.M. IN 36"X8" M.O.S. S 35° E 46.2' FROM ORIGINAL NORTHWEST BEARING TREE, F.W.B. A 4" 36" ROTTED FIR STUMP S 61° 27' W 25.8' (REC. 24" P. PINE S 30° W 40 LKS.), A 9" CEDAR S 57° 18' W 45.2' MKD. 1/4 S 35 BT, AN 8" CEDAR S 19° 49' W 28.6' MKD. 1/4 S 35 BT.
10 SEC. COR. SEC'S. 26, 27, 34 AND 35, NO EVIDENCE FOUND, POSITION DETERMINED BY DOUBLE PROPORTIONATE MEASUREMENTS. SET A U.S.F.S. S.S.M. IN A 34"X30" M.O.S., F.W.B. A 21" D. FIR N 0° 09' W 23.4' MKD. T26 NR 9 E S 27 BT, A 16" P. PINE S 26° 20' E 30.6' MKD. T26 NR 9 E S 35 BT, A 5" B. OAK S 47° 02' W 47.9' MKD. T26 NR 9 E S 34 BT.

CORNER

- 11 E 1/16 COR. SEC'S. 27 AND 34, SET 5/8" DRIVE-IN MONUMENT WITH CAP, STAMPED WITH APPROPRIATE MARKINGS, F.W.B. A 6" OAK N 22° E 19.2' MKD. E 1/16 S 27 BT, A 5" OAK S 6° W 21.8' MKD. E 1/16 S 34 BT.
12 SE 1/16 COR. SEC. 27, SET 5/8" DRIVE-IN MONUMENT WITH CAP, STAMPED WITH APPROPRIATE MARKINGS F.W.B. A 6" P. PINE N 82° W 5.0' MKD. SE 1/16 S 27 BT, A 7" W. FIR S 2° E 7.9' MKD. SE 1/16 S 27 BT.
13 1/4 COR. SEC'S. 26 AND 27, (REC. 12"X10"X6" STONE IN STONE MOUND) FOUND A 2 3/8" ALUMINUM CAPPED MONUMENT IN 30"X9" M.O.S. SET BY C.A.F. IN 1976. (REC. 40" FIR S 40° W 55 LKS.) FOUND A 72" FIR STUMP HOLE S 39° 56' W 36.9' AND A 2 5/8" FIR LAYING DOWN HILL APPROX. 46' FROM THE STUMP HOLE, BARK SCRIBED WITH 1/4 S BT LEGIBLE. MKD. A 15" D. FIR S 34° 16' E 7.7' MKD. 1/4 S 26 BT, A 24" D. FIR N 85° 39' W 9.0' MKD. 1/4 S 27 BT.
14 CE 1/16 COR. SEC. 27, SET A U.S.F.S. S.S.M., F.W.B. A 18" D. FIR N 84° 18' E 14.9' MKD. CE 1/16 S 27 BT, A 14" D. FIR N 84° 14' W 36.5' MKD. CE 1/16 S 27 BT.
15 C 1/4 COR. SEC. 27, SET A U.S.F.S. S.S.M. IN A 24"X10" M.O.S., F.W.B. A 12" D. FIR N 35° 30' W 4.8' MKD. C 1/4 S 27 BT, A 11" W. FIR N 72° E 23.6' MKD. C 1/4 S 27 BT.
16 1/4 COR. SEC'S. 27 AND 28, NO EVIDENCE FOUND, POSITION DETERMINED BY SINGLE PROPORTIONATE MEASUREMENTS. SET A U.S.F.S. S.S.M. IN A 36"X8" M.O.S., F.W.B. A 45" S. PINE S 41° 52' E 26.0' WITH OPEN FACE AND K-TAGS, A 5" CEDAR S 15° 35' E 17.4' MKD. 1/4 S 27 BT, A 19" D. FIR N 16° 51' W 24.0' MKD. 1/4 S 28 BT.
17 CS 1/16 SEC. 27, MKD. A 26" P. PINE FOR THE COR. WITH CS 1/16 S 27 ON THE NORTH AND EAST SIDES. SET A REFERENCE MONUMENT, A 5/8" DRIVE-IN MONUMENT WITH CAP, STAMPED WITH APPROPRIATE MARKINGS, N 48° 57' 22" E 6.9' FROM THE TREE COR.
18 1/4 COR. SEC'S. 27 AND 34, NO EVIDENCE FOUND, POSITION DETERMINED BY SINGLE PROPORTIONATE MEASUREMENTS. SET A 5/8" DRIVE-IN MONUMENT WITH CAP, STAMPED WITH APPROPRIATE MARKINGS, F.W.B. A 7" P. PINE N 62° 55' E 12.5' MKD. 1/4 S 27 BT, A 8" CEDAR S 7° 21' W 13.8' MKD. 1/4 S 34 BT.
19 W 1/16 COR. SEC'S. 27 AND 34, SET A 5/8" DRIVE-IN MONUMENT WITH CAP, STAMPED WITH APPROPRIATE MARKINGS, F.W.B. A 14" P. PINE S 62° 30' E 21.0' MKD. W 1/16 S 34 BT, A 19" P. PINE N 72° E 21.6' MKD. W 1/16 S 27 BT.
20 NW 1/16 COR. SEC. 34, MKD. A 4" ON ROCK OUTCROP AT TRUE COR. POSITION, F.W.B. A 8" P. PINE S 62° W 30.7' MKD. NW 1/16 S 34 BT, A 21" CEDAR S 42° E 34.8' MKD. NW 1/16 S 34 BT. SET A REFERENCE MONUMENT, A 5/8" DRIVE-IN MONUMENT WITH CAP, STAMPED WITH APPROPRIATE MARKINGS, S 85° 29' E 9.7' FROM THE COR.
21 1/4 COR. SEC'S. 34 AND 35, FOUND A STD. B.L.M. BRASS CAP MONUMENT SET IN 1973, F.W.B. A 13" D. FIR S 83° W 8.4' WITH OPEN FACE, BT VISIBLE, A 7" B. OAK N 11° E 27.5' WITH HEALED FACE AND BT-TAG, A 7" D. FIR S 5° E 25.8' WITH HEALED FACE AND BT-TAG.
22 1/4 COR. SEC. 35 ONLY, (REC. 13"X8"X4" SLATE STONE) FOUND A 2 1/2" ALUMINUM CAPPED MONUMENT IN A 30" DIA. OLD EMBEDDED M.O.S. SET BY C.A.F. IN 1976 WITH A 15"X3"X4" STONE FAINTLY MARKED ALONGSIDE, F.W.B. A 33" DEAD STANDING PINE SNAG S 42° 22' W 8.7' WITH OPEN BURNED OUT BLAZE AND ILLEGIBLE SCRIBING (REC. 30" P. PINE S 44° W 11 LKS.)

CORNER

- 23 1/4 COR. SEC. 34 ONLY, NO EVIDENCE FOUND, POSITION DETERMINED BY IRREGULAR BOUNDARY ADJUSTMENT METHOD AND FALLS ON STEEP LOOSE FILL BETWEEN R R GRADE AND INDIAN CREEK. N 89° 33' 01" E 27.17' FROM TRUE COR. POSITION; SET U.S.F.S. S.S.M. FOR WITNESS COR. ON R R GRADE, F.W.B. A 12" D. FIR S 86° 59' W 77.3' MKD. X AND BT, A U.S.G.S. B.M. MONUMENT S 52° 55' 30" W 223.46' SET IN CONCRETE ON NW ABUTMENT OF R R BRIDGE.
24 SEC. COR. SEC'S. 33 AND 34, FOUND A STD. B.L.M. BRASS CAP MONUMENT IN A 30"X12" M.O.S. SET IN 1967, A 5" L. OAK N 38° 15' W 37.9', A STUMP HOLE WITH DOWN, DEAD 36" P. PINE N 20° 20' E 29.4', A 7" L. OAK N 72° 29' E 20.8', A 35" S. PINE S 48° 54' E 27.9'.
25 1/4 COR. SEC'S. 33 AND 34 (REC. 12"X14"X8" STONE) FOUND A 2 1/2" ALUMINUM CAPPED MONUMENT IN 30"X12" M.O.S. SET BY C.A.F. IN 1971, F.W.B. A 26" P. PINE N 70° 34' E 48.5' WITH OPEN BLAZE AND VISIBLE SCRIBING (REC. 12" P. PINE N 72° 32' E 73 LKS.), A 9" D. FIR S 77° W 18.8' MKD. 1/4 S 33 BT, AN 18" P. PINE S 72° 30' E 60.8' MKD. 1/4 S 34 BT.
26 N 1/16 COR. SEC'S. 33 AND 34, N 53° 30' 37" W 46.55' FROM TRUE N 1/16 COR. POSITION, FOUND A U.S.F.S. S.S.M. SET BY L.S. 4388 AND RECORDED IN G.R.S. 28, F.W.B. A 9" D. FIR S 53° 03' E 21.7' WITH PARTIALLY HEALED BLAZE AND SCRIBING, A 5" D. FIR S 71° 26' W 4.1' WITH PARTIALLY HEALED BLAZE AND SCRIBING, SOUTHERLY BOUNDARY OF NW 1/4 OF NW 1/4 OF SEC. 34 POSTED TO TRUE N 1/16 COR. POSITION. NOTHING SET.
27 SEC. COR. SEC'S. 27, 28, 33 AND 34. (REC. 10"X3"X3" STONE) FOUND A 2 1/2" ALUMINUM CAPPED MONUMENT IN 36" DIA. M.O.S. SET BY C.A.F. IN 1976 WITH 24"X12"X4" STONE ALONGSIDE, F.W.B. A 48" FIR STUMP N 84° 47' E 17.2' WITH BT TAG (REC. A 36" FIR N 60° 31' E 12 LKS), A 36" P. PINE STUMP S 38° 22' W 69.2' WITH SCRIBING. REMNANT NAILED TO BASE (REC. A 24" P. PINE S 37° 34' W 103 LKS). FROM COR. MONUMENT, NEW BEARING TREES ARE 9" CEDAR N 49° E 54.2' MKD. T26 NR 9 E S 27 BT, A 7" CEDAR S 27° E 31.3' MKD. T26 NR 9 E S 34 BT, A 8" CEDAR S 26° W 8.3' MKD. T26 NR 9 E S 33 BT, A 9" CEDAR N 36° 30' W 3.9' MKD. T26 NR 9 E S 28 BT.

RECORD OF SURVEY

FOR THE UNITED STATES FOREST SERVICE AND COLLINS PINE, IN SECTIONS 27 AND 34, T.26 N., R. 9 E., M.D.M., IN THE UNINCORPORATED AREA OF PLUMAS COUNTY, STATE OF CALIFORNIA.

ROBERT GRAUBERGER L.S. 5287

AUGUST 1984 SHEET 2 OF 2