

T25N R5E WC  
S32 | S33  
55 | 54  
T24N  
LS3966  
1985

**CORNER NO. 1**

FD. 30"x5 1/2"x14" STONE IN STONE MOUND - SET STD. USFS ALUM. MON. IN MOUND OF ROCKS

T25N R5E  
S32 | S33  
55 | 54  
T24N  
LS3966  
1985

**CORNER NO. 2**

SET STD. USFS ALUM. MON. IN MOUND OF ROCKS - SET BY SINGLE PROPORTION CORNER IS 250' EAST OF A NORTH SOUTH CLIFF

A 6" PINE BEARS N53°W 145.1' SCRIBED FOR BT

A 7 1/2" PINE BEARS S53°W 87.7' SCRIBED FOR BT

T25N R5E  
S33 | S34  
54 | 53  
T24N  
LS3966  
1985

**CORNER NO. 3**

FD. 20"x14"x7" STONE IN STONE MOUND SET STD. USFS ALUM. MON. IN MOUND OF ROCKS - CORNER FALLS IN BRUSHY SADDLE, APPROX. 300' NORTH OF BRUSHY KNOB AND 200' SOUTH OF TIMBER LINE.

A 8" RED FIR BEARS N58°E 90.8' SCRIBED FOR BT

T25N R5E  
1/4 | S34  
S3  
T24N  
LS3966  
1985

**CORNER NO. 4**

SET STD. USFS ALUM. MON. IN MOUND OF ROCKS - SET BY SINGLE PROPORTION

A 6" FIR BEARS N37°E 43.3' SCRIBED FOR BT

A 8" FIR BEARS S62°E 19.7' SCRIBED FOR BT

T25N  
S34 | S35  
S3 | S2  
T24N  
LS3966  
1985

**CORNER NO. 5**

SET STD. USFS ALUM. MON. IN MOUND OF ROCKS

FD. 22" LODGEPOLE SWAG - N64°E 5.3' - V.S. (N64°E 5.3' - GLO)

FD. 18" LODGEPOLE - S45°W 5.9' - V.S. (S45°W 5.3' - GLO)

FD. STUMP & 20" DOWN LODGEPOLE - N45°W 9.2' - V.S. (N45°W 9.2' - GLO)

A 14" CEDAR BEARS N37°W 18.9' SCRIBED FOR BT

A 12" FIR BEARS N20°E 42.4' SCRIBED FOR BT

T24N R5E  
1/4  
S5 | S4  
LS3966  
1985

**CORNER NO. 6**

SET STD. USFS ALUM. MON. IN MOUND OF ROCKS - SET BY SINGLE PROPORTION

A 10" WHITE FIR BEARS N2°W 4.7' SCRIBED FOR BT

A 5" BLACK OAK BEARS S59°E 33.3' SCRIBED FOR BT

T25N R5E  
1/4  
S4 | S3  
LS3966  
1985

**CORNER NO. 7**

NO GLO EVIDENCE FOUND - SET BY SINGLE PROPORTION - SET STD. USFS ALUM. MON. IN ROCK MOUND - 5' DIA. AND 2' HIGH

MARKED B.O. ROCK PROTRUSION 2 1/2 FT. HIGH ON FACE BY 4 FT. WIDE WITH 3/4" BRASS WASHER MKD. LS3966 AT CENTER OF ON TOP OF THE POINT OF PROTRUSION - WASHER BEARS N40°E 22.7'

A 12" PINE BEARS S56°W 30.3' SCRIBED FOR BT

T24N R5E  
1/4  
S3 | S2  
LS3966  
1985

**CORNER NO. 8**

SET STD. USFS ALUM. MON. IN MOUND OF ROCKS - SET BY SINGLE PROPORTION CORNER FALLS ON EAST SLOPE 300' + NORTH OF RIDGE

A 8" WHITE FIR BEARS N46°W 10.1' SCRIBED FOR BT

A 11" WHITE FIR BEARS N19°E 15.8' SCRIBED FOR BT

**NOTE**  
GLO NOTES SHOW THIS CORNER SET AT THE MIDPOINT OF A LINE 80.60 CHAINS LONG. THIS BEING THE ONLY NORTH TIER LINE THAT IS MID-POINTED. I TAKE THIS TO BE A MISTAKE IN NOTE WRITING AND SET THE CORNER AT A PROPORTIONED 40 CHAINS FROM THE SOUTH AND 40.60 CHAINS FROM THE NORTH.

T24N R5W  
1/4  
S2 | S1  
LS3966  
1985

**CORNER NO. 9**

FD. STONE MOUND - SET STD. USFS ALUM. MON. IN MOUND OF ROCKS

FD. 34" Y. PINE - N11°W 34.2' TO CTR. - H.B. (12" Y. PINE - N11 1/2°W 33.7' - GLO)

A 12" FIR BEARS S61°E 9.1' SCRIBED FOR BT

**CORNER NOTES**

V.S. = VISIBLE SCRIBING  
H.B. = HEALED BLAZE

T24N R5E  
S5 | S4  
S8 | S9  
LS3966  
1985

**CORNER NO. 10**

FD. SMALL STONE MOUND - SET STD. USFS ALUM. MON. IN MOUND OF ROCKS

FD. 10'x10' GRANITE ROCK - N81°W 71.0' (10'x10' GRANITE ROCK - N81°W 89.1' - GLO)

FD. 15'x10' GRANITE ROCK - S64°E 44.9' (15'x10' GRANITE ROCK - S64°E 44.9' - GLO)

A 13" BLACK OAK BEARS N26°W 5.3' SCRIBED FOR BT

T24N R5E  
1/4 | S4  
S9  
LS3966  
1985

**CORNER NO. 11**

SET STD. USFS ALUM. MON. IN MOUND OF ROCKS - SET BY SINGLE PROPORTION

A 6" BLACK OAK BEARS N32°E 9.0' SCRIBED FOR BT

A 4" BLACK OAK BEARS S64°E 3.4' SCRIBED X AT BREAST HT. AND BT NEAR BOTTOM

T24N R5E  
S4 | S3  
S9 | S10  
LS3966  
1985

**CORNER NO. 12**

SET STD. USFS ALUM. MON. IN MOUND OF ROCKS - SET BY DOUBLE PROPORTION

A 6" WHITE FIR BEARS S44°E 26.0' SCRIBED T24N R5E S10 BT

A 6 1/2" WHITE FIR BEARS S61°W 6.2' SCRIBED T24N R5E S9 BT

A 9" FORKED WHITE FIR BEARS N62°W 9.1' SCRIBED T24N R5E S4 BT

A 14" WHITE FIR BEARS N22°E 16.5' SCRIBED T24N R5E S3 BT

T24N R5E  
S3 | S2  
S10 | S11  
LS3966  
1985

**CORNER NO. 13**

FD. 1" O. D. OPEN GALV. PIPE IN SMALL M.O.R. - SET STD. USFS ALUM. MON. IN MOUND OF ROCKS

FD. 54" SUGAR PINE - S5°W 39.7' - V.S. (S36°W 3.96' - GLO)

FD. 15" CEDAR - S80°E 52.8' - V.S.

FD. 40" RED FIR - N17°E 7.2' - V.S. (N21°E 5.9' - GLO)

FD. 19" CEDAR - N31°W 59.6' - V.S.

T24N R5E  
1/4 | S2  
S11 | S12  
LS3966  
1985

**CORNER NO. 14**

SET 3 1/2" USFS ALUM. MON. IN DRILL HOLE IN NE END OF BOULDER (6'x3'x2' OF BOULDER EXPOSED.) CAP IS APPROX. 12" ABOVE GROUND LEVEL. SET BY SINGLE PROPORTION

A 8" FIR BEARS N20°E 10.3' SCRIBED FOR BT

A 8" FIR BEARS S12°E 20.7' SCRIBED FOR BT

T24N R5E  
S2 | S1  
S11 | S12  
LS3966  
1985

**CORNER NO. 15**

FD. 16"x14"x8" STONE IN STONE MOUND SET STD. USFS ALUM. MON. IN MOUND OF ROCKS - CORNER FALLS ON STEEP ROCKY WEST SLOPE

A 27" DOUG. FIR BEARS N76°W 70.9' SCRIBED FOR BT

CHISELED X ON A HUGE BOULDER - N60°E 10.9'

T24N R5E  
1/4  
S8 | S9  
LS3966  
1985

**CORNER NO. 16**

FD. MOUND OF STONE - SET STD. USFS ALUM. MON. IN MOUND OF ROCKS

FD. 49" YELLOW PINE - S60°W 78.5' TO CTR. TREE - V.S. (S58 1/2°W 76.6' - GLO)

A 7" WHITE FIR BEARS N48°E 39.0' SCRIBED FOR BT

T24N R5E  
S9 | S10  
S16 | S15  
LS3966  
1985

**CORNER NO. 17**

FD. SMALL, DEEPLY IMBEDDED STONE MOUND SET STD. USFS ALUM. MON. IN MOUND OF ROCKS - CORNER FALLS ON BRUSHY GENTLE WEST SLOPE 200' EAST OF ROAD

FD. W. FIR STUMP - S66°W 50.8' (S75°W 50.8' - GLO)

FD. W. FIR STUMP - N85°W 29.0' (N83°W 29.0' - GLO)

A 8" FIR BEARS S62°W 48.6' SCRIBED FOR BT

A 6" FIR BEARS N67°W 35.3' SCRIBED FOR BT

A 4" FIR BEARS N55°E 26.3' SCRIBED X BREAST HIGH, BT NEAR BOTTOM

A 4" FIR BEARS S43°E 6.3' SCRIBED X BREAST HIGH, BT NEAR BOTTOM

T24N R5E  
1/4  
S11 | S12  
LS3966  
1985

**CORNER NO. 18**

FD. STONE MOUND - SET STD. USFS ALUM. MON. IN MOUND OF ROCKS CORNER FALLS ON EAST SLOPE, STEEP AND ROCKY

FD. DOWN & ROTTEN B. OAK STUMP HOLE - N28°W 7.1' (8" BLACK OAK - N28°W 5.3' - GLO)

FD. 41" SUGAR PINE - S71°E 8.1' TO CTR. TREE (20" SUGAR PINE - S71°E 7.9' - GLO)

A 8" DOUG. FIR BEARS N25°W 7.1' SCRIBED FOR BT

T24N R5E  
S11 | S12  
S14 | S13  
LS3966  
1985

**CORNER NO. 19**

SET STD. USFS ALUM. MON. IN MOUND OF ROCKS

FD. 17" CEDAR BT - N11°W 32.3' - V.S. (N10°W 31.7' - GLO)

FD. 23" CEDAR BT - N7°E 39.3' - H.B. (N6 1/2°E 38.3' - GLO)

FD. 12" BLACK OAK BT - S15°E 14.3' - H.B. (S9°E 14.5' - GLO)

FD. 41" DOUG. FIR BT - S20°W 16.7' - H.B. (S20°W 17.8' - GLO)

T24N  
S12 | R5E  
S13 | S7  
R5E  
1938

**CORNER NO. 20**

FD. 1938 GLO BRASS CAP ON IRON PIPE IN MOUND OF ROCKS

FD. MAPLE DEAD AND DOWN (7" MAPLE - N20 1/2°E 25.1' - GLO)

FD. REMAINS OF OAK - S31 1/4°E 12.5' (20" BLACK OAK - S31 1/4°E 12.5' - GLO)

FD. REMAINS OF OAK - S44°W 14.5' (12" BLACK OAK - S44°W 14.5' - GLO)

FD. 38" FIR - N63°W 24.4' - H.B. (30" FIR - N63°W 24.4' - GLO)

FD. 32" CEDAR - N25°W 36.3' - H.B. (20" CEDAR - N25°W 36.3' - GLO)

1/4 | S13  
1938

**CORNER NO. 21**

FD. 1938 GLO B.C. IN STONE MOUND 66' NORTH OF CREEK

FD. 53" DOUG. FIR BT - S67°E 38.9' - V.S. (48" RED FIR - S67°E 38.9' - GLO)

FD. 31" CEDAR - S77°W 38.3' - V.S. (24" CEDAR - S77°W 38.3' - GLO)

A 12" WHITE FIR BEARS N33°W 11.2' SCRIBED FOR BT

T24N  
R5E | R5E  
S13 | S18  
S24 | AP2  
TR38  
1938

**CORNER NO. 22**

FD. 1938 GLO PIPE AND BRASS CAP IN STONE MOUND

FD. REMAINS OF DOWN AND ROTTEN OAK BT S42°W 35.6'


FD. 13" BLACK OAK BT - N65°W 86.5' - H.B.

A 15" Y. PINE BEARS S24°W 23.9' - SCRIBED FOR BT

**RECORD OF SURVEY**

FOR  
THE USDA FOREST SERVICE  
AND  
DIAMOND INTERNATIONAL

IN SECTIONS 1 THRU 5 AND 8 THRU 13, T24N, R5E, M.D.M., AND IN THE COUNTY OF BUTTE & COUNTY OF PLUMAS, STATE OF CALIFORNIA

 DEL TERRA, INC.  
SURVEYING  
REDDING, CA.

DATE NOVEMBER 1985  
SHEET 2 OF 2