

CORNER NOTES

25N R9E  
S 1/4  
S7 | S8  
LS 4976  
1967

SET: STANDARD ACAP IN M.D.S. STAMPED AS SHOWN.  
F.W.B.: 7" V. PINE N19°E 10.3 Ft. Mkd. "S 1/16 S8 BT" (NEW)  
8" V. PINE N46°W 7.9 Ft. Mkd. "S 1/16 S7 BT" (NEW)

1/4  
T25N R9E  
S7 | S8  
1967

FOUND: 3 1/4" B.C. IN M.D.S. STAMPED AS SHOWN.  
F.W.B.: FOUND ROTTED LOG LYING DOWNHILL OF STUMP HOLE  
W/ SCRIBING "1/4 S BT" VISIBLE S63°W 6.2 FT.  
(12" S. PINE S71 1/4°W 5 1/2 Ks. - GLO)  
20" D. FIR W/ FACE AND AXE MARKS POSSIBLE ORIGINAL  
SE BT S37 1/2°E 8.7 FT. (15" S. PINE S57 1/2°E 14 1/2 Ks. - GLO)  
20" S. PINE W/ CLOSED FACE N49°E 16.8 FT. (18" S. PINE  
N50°E 27 1/2 Ks. - BLM 1967)  
16" D. FIR W/ CLOSED FACE S84 1/2°W 22.1 FT. (13" FIR  
S83°W 35 Ks. - BLM 1967)

25N R9E  
C 1/4  
S7  
LS 4976  
1967

SET: STANDARD ACAP IN M.D.S. STAMPED AS SHOWN.  
F.W.B.: 18" CEDAR S32°E 4.7 Ft. Mkd. "C 1/4 S7 BT" (NEW)  
12" W. FIR S52°W 8.0 Ft. Mkd. "C 1/4 S7 BT" (NEW)

25N R9E  
W 1/16  
C 3/4  
LS 4976  
1967

SET: STANDARD ACAP IN M.D.S. STAMPED AS SHOWN.  
CORNER FALLS ON CUT SLOPE BETWEEN TWO  
LOGGING ROADS.  
F.W.B.: 4" D. FIR S21°E 2.0 Ft. Mkd. "X" BT" (NEW)  
8" D. FIR N72°W 18.6 Ft. Mkd. "W 1/16 S7 BT" (NEW)

25N R9E  
S 1/4  
S6 | S7  
LS 4976  
1967

SET: STANDARD ACAP IN M.D.S. STAMPED AS SHOWN.  
F.W.B.: 22" V. PINE N54°W 16.7 Ft. Mkd. "W 1/16 S6 BT" (NEW)  
6" D. FIR S19°W 39.7 Ft. Mkd. "W 1/16 S7 BT" (NEW)  
3 1/4" ACAP ON EDGE OF LOGGING ROAD STAMPED "W 1/16  
S6 S7 1979 LS 4388" (L.R.S. 26) S 42°38'26"W 28.95 Ft.

25N R9E  
S 1/4  
S6 | S7  
LS 4976  
1967

FOUND: NOTHING AT CORNER POSITION. FOUND REMAINS OF SE BT.  
CORNER FALLS IN LARGE MANZANITA PATCH. FOUND VERY  
OLD CUT ENDS OF MANZANITA BETWEEN SE BT AND  
CORNER POSITION. CORNER FITS POSITION WELL FOR  
STUBBED LINE FROM WEST (SECTION CORNER TO SECTION 5,  
6, 7 & 8). INDICATIONS FROM SOUTH LINE SECTION 7  
AND SOUTH LINE SECTION 18. WEST RUNNING LINES  
WERE NEVER CLOSED ON THE RANGE LINE AS INDICATED  
IN THE ORIGINAL NOTES. SET STANDARD ACAP IN M.D.S. AS SHOWN.

F.W.B.: DEAD & DOWN BURNT 24" S. PINE W/ AXE MARKS AND  
BURNT FACE S7 1/2°E 23.8 Ft. (20" S. PINE S7 1/2°E  
36 Ks. - GLO)  
7" V. PINE N66°W 10.1 Ft. Mkd. "1/4 S6 BT" (NEW)  
14" V. PINE S23°W 13.7 Ft. Mkd. "1/4 S7 BT" (NEW)

25N R9E  
E 1/4  
S6 | S7  
LS 4976  
1967

SET: STANDARD ACAP IN M.D.S. STAMPED AS SHOWN.  
F.W.B.: 22" CEDAR S15°W 17.2 Ft. Mkd. "E 1/16 S7 BT" (NEW)  
5" D. FIR N46°W 14.8 Ft. Mkd. "X" BT" (NEW)  
3 1/4" ACAP STAMPED "E 1/16 S6 S7 LS 4388 1979"  
N14°50'51"W 84.85 Ft. (L.R.S. 26)

25N R9E  
S 1/4  
S6 | S5  
S7 | S8  
LS 4976  
1967

FOUND: SCATTERED M.D.S. UNDER DOWN ± 30° PINE (NE BT) 1.44 Ch. EAST OF SE RUNNING SPRING (5.05 Ch. - GLO). CORNER FITS RAVINE CALLS TO THE WEST (8.25 Ch. & 17.50 Ch.). RAN OUT TOPO CALLS TO THE SOUTH, CORNER FITS STREAM CALLS 67.15, 71.65 & 74.40 Ch. SET STANDARD ACAP IN M.D.S. AS SHOWN.

F.W.B.: 2 1/4" B. OAK (DOWN) W/ AXED FACE (NEVER HEALED) SCRIBING NOT VISIBLE N14°W 25.2 FT. (10" B. OAK N15°W 38 1/2 Ks. - GLO)  
130" DEAD AND DOWN V. PINE W/ FACE AND CHAINING NOTCH NO SCRIBING N29°E 58.6 FT. (28" V. PINE N31 1/2°E 58 1/2 Ks. - GLO). TREE FELL ON CORNER.  
ROTTED OAK STUMP W/ FACE POSSIBLE SCRIBING REVERSE "B" S19°E 23.4 FT. (10" B. OAK S24°E 35 1/2 Ks. - GLO)  
22" V. PINE S87°W 30.6 FT. Mkd. "T25N R9E S7 BT" (NEW)  
14" D. FIR SOUTH 10.6 Ft. Mkd. "T25N R9E S8 BT" (NEW)  
6 1/2" D. FIR N27°W 8.4 Ft. Mkd. "T25N R9E S6 BT" (NEW)  
10" D. FIR EAST 31.7 Ft. Mkd. "T25N R9E S5 BT" (NEW)  
3 1/4" ACAP IN M.D.S. STAMPED "T25N R9E S5 S6 S7 S8 1979 LS 4388" N0°26'13"W 209.22 Ft. (L.R.S. 26)

25N R9E  
1/4  
S6 | S5  
LS 4976  
1967

FOUND: NOTHING AT CORNER POSITION. FOUND SW BT, SET STANDARD ACAP IN M.D.S. AT RECORD BEARING AND DISTANCE. CORNER POSITION FITS RELATIVE CALLS TO THE NORTH, DOES NOT FIT CALLS TO THE SOUTH. DUE TO THE EXCESS IN THE SOUTH PORTION OF THE SECTION LINE IT APPEARS THIS QUARTER CORNER WAS STUBBED IN FROM THE NORTH.

F.W.B.: 8" CEDAR W/ CLOSED FACE, CUT INTO FACE, AND FOUND SCRIBING "1/4 S BT" S76°W 21.8 Ft. (6" CEDAR S76°W 33 Ks. - GLO)  
± 30" DEAD AND DOWN PINE S44°E 30.9 Ft. (33.9 FT SLOPE DIST.) (30" V. PINE S61°E 52 1/2 Ks. - GLO)  
18" S. PINE S82°W 40.4 Ft. Mkd. "1/4 S6 BT" (NEW)  
18" D. FIR N38°E 61.1 Ft. Mkd. "1/4 S5 BT" (NEW)

25N R9E  
S 3/4  
S6 | S5  
C L  
T25N R9E  
1967

FOUND: 3 1/4" B.C. IN M.D.S. STAMPED AS SHOWN.  
F.W.B.: 11" B. OAK W/ OPEN FACE, FOUND REVERSE SCRIBING "T" N74°E 31.1 Ft. (10" B. OAK N77°E 47 1/2 Ks. - GLO)  
7" B. OAK W/ CLOSED FACE S78 1/2°W 6.3 Ft. (7" B. OAK S77°W 10 1/2 Ks. - BLM 1967)  
13" D. FIR W/ CLOSED FACE S27 1/2°E 16.5 Ft. (10" FIR S26°E 25 1/2 Ks. - BLM 1967)  
3 1/4" ACAP IN M.D.S. STAMPED "T26N R9E S31 T25N R9E S6 S5 AM CC 1979 LS 4388" (L.R.S. 26)  
S00°D1 47°W 51.40 (N0°18'33"W 51.88 6RS26)

25N R9E  
1/4  
S12 | S7  
LS 4976  
1967

FOUND: NOTHING AT CORNER POSITION. FOUND REMAINS OF BOTH BT'S. SET STANDARD ACAP STAMPED AS SHOWN AT DIST-DIST. INTERSECTION. CORNER FITS CALLS WELL.  
F.W.B.: OAK STUMP HOLE AND PARTIAL FACE W/ REVERSE SCRIBING VISIBLE S15°E 31.7 Ft. (8" B. OAK S17°E 48 Ks. - GLO)  
44" FIR STUMP (ONLY + 40 INCH FIR IN VICINITY) N35°E 4.0 Ft. (40" FIR N35°E 6 1/2 Ks. - GLO)  
10" W. FIR N89°E 33.9 Ft. Mkd. "1/4 S7 BT" (NEW)  
7" S. PINE N18°W 27.1 Ft. Mkd. "1/4 S12 BT" (NEW)

RECORD OF SURVEY  
U.S.D.A. - PLUMAS NATIONAL FOREST  
'SODA CADASTRAL SURVEY'