

CORNER NOTES

① T24N R10E
518 514
522 523
1971
B.L.M.

FOUND: 3/4" BRASS CAP IN M.O.S. STAMPED AS SHOWN.
F.W.B.: 23" 4. PINE WITH BLAZE AND SCRIBING "XV" VISIBLE N52°E 11.8 FT.
(16" 3. PINE N53°40'E 171ks. -G.L.D.)
20" B. OAK WITH HEALED BLAZE S42°40'E 37.1 FT.
(20" B. OAK S42°40'E 561ks. -G.L.D.)
B. OAK STUMP HOLE S10°W 20.7 FT. (B" B. OAK S10°12'W 331ks. -G.L.D.)
STUMP HOLE N66°1/2'W 15.1 FT. (10" B. OAK N70°1/2'W 221ks. -G.L.D.)
28" 4. PINE WITH BLAZE AND SCRIBING VISIBLE S41°W 40.9 FT.
(28" 4. PINE S41°W 721ks. -BLM)
16" B. OAK WITH BLAZE AND SCRIBING VISIBLE N59°W 55.3 FT.
(16" B. OAK N59°W 851ks. -BLM)
12" 4. PINE WITH BLAZE AND SCRIBING VISIBLE S16°1/2'E 25.3 FT. (No Record)

② T24N R10E
1/4 523
1971
B.L.M.

FOUND: 3/4" BRASS CAP IN M.O.S. STAMPED AS SHOWN.
F.W.B.: STUMP HOLE N50°1/2'E 28.8 FT. (10" B. OAK N50°34'E 421ks. -G.L.D.)
25" B. OAK WITH BLAZE AND SCRIBING VISIBLE S64°W 13.8 FT.
(13" B. OAK S63°34'W 211ks. -G.L.D.)
8" D. FIR WITH CLOSED BLAZE N52°E 24.3 FT. (7" FIR N52°E 361ks. -BLM)
8" CEDAR WITH CLOSED BLAZE S32°1/2'E 29.1 FT. (6" CEDAR S32°E 451ks. -BLM)

③ T24N R10E
523 524
1971
B.L.M.

FOUND: 3/4" BRASS CAP IN M.O.S. STAMPED AS SHOWN.
F.W.B.: 28" PINE WITH HEALED BLAZE S61°1/2'W 8.1 FT. (18" 4. PINE S59°W 121ks. -G.L.D.)
10" HIGH 13" PINE SNAG WITH SCRIBING VISIBLE S69°E 9.8 FT.
(10" 4. PINE S63°E 141ks. -G.L.D.)
13" D. FIR WITH HEALED BLAZE S69°E 17.3 FT. (10" D. FIR S67°E 261ks. -BLM)

④ T24N R10E
523 524
620 528
LS 49716
1986

FOUND: NOTHING AT CORNER POSITION. SET 2 1/2" x 30" ACAP STAMPED AS SHOWN FROM BEST FIT OF 3 FOUND ORIG. BEARING TREES.
F.W.B.: 16" 4. PINE WITH SCRIBING "XXIV RXE 5 BT" VISIBLE S47°W 15.8 FT.
(6" 4. PINE S45°W 241ks. -G.L.D.)
15" CEDAR WITH SCRIBING "XXIV RXE SXXVII" VISIBLE N71°W 26.4 FT. (8" RED FIR N 84°W 401ks. -G.L.D.)
24" D. FIR CUT PLUS AND FOUND SCRIBING "XXIV (1" RING COUNTS ±100 YEARS N23°E 30.0 FT. (10" CEDAR N25°E 411ks. -G.L.D.)
18" 4. PINE S83°E 32.5 FT. Mkd. "T24N R10E S25 BT" (NEW)
17" 4. PINE N4°E 26.9 FT. Mkd. "T24N R10E S24 BT" (NEW)

⑤ T24N R10E
1/4 522
526
LS 49716
1986

FOUND: DOWN AND ROTTED PINE WITH AXED FACE AND SCRIBING "1" VISIBLE. PINE CUT AT BOTTOM OF BLAZE. MATCHING STUMP NOT RECOVERED. PROBABLE LOCATION OF ORIGINAL CORNER AT 1/4 IN EDGE OF RAILROAD FILL AS INDICATED BY DISTANCE TIE ON RAILROAD R/W MAPS. CORNER LOST AND SET 2 1/2" x 30" ACAP AT SINGLE PRORATE POSITION, STAMPED AS SHOWN.
F.W.B.: 11" 4. PINE S66°W 13.2 FT. Mkd. "1/4 S26 BT" (NEW)
16" 4. PINE N40°W 131.3 FT. Mkd. "1/4 S23 BT" (NEW)

⑥ T24N R10E
522 523
527 526
1971
B.L.M.

FOUND: 3/4" BRASS CAP IN M.O.S. STAMPED AS SHOWN.
F.W.B.: DOWN 10" B. OAK WITH SCRIBING VISIBLE S64°W 86.2 FT.
(10" B. OAK S63°W 1231ks. -G.L.D.)
9" B. OAK WITH POSSIBLE BLAZE N30°E 77.1 FT. (8" B. OAK N35°E 1151ks. -G.L.D.)
44" 4. PINE WITH HEALED BLAZE S19°E 20.8 FT. (30" PINE S15°E 301ks. -G.L.D.)
STUMP HOLE N60°E 13.5 FT. (36" PINE N71°1/2'E 191ks. -G.L.D.)
6" FIR WITH HEALED BLAZE N21°E 10.4 FT. (5" FIR N20°E 161ks. -BLM)
9" W. FIR WITH HEALED BLAZE S80°E 16.3 FT. (7" FIR S80°E 251ks. -BLM)
9" W. FIR WITH HEALED BLAZE S53°W 5.4 FT. (8" FIR S60°W 81ks. -BLM)
10" CEDAR WITH BLAZE AND SCRIBING VISIBLE N27°1/2'W 19.9 FT.
(8" CEDAR N27°N 301ks. -BLM)

⑦ T24N R10E
1/4 522 523
527 526
LS 49716
1986

FOUND: NOTHING FOUND. FOUND ±48" PINE STUMP WITH HEALED BLAZES, NO SCRIBING, ON SOUTH, WEST AND EAST SIDES. BLAZES WERE ANALYZED AND AGE DATED AT DENDROLOGY LAB, UNIV. OF ARIZONA, TULSON, ARIZONA, AND DATED BLAZES BETWEEN 1911 AND 1912 (ORIGINAL SURVEY - 1880). FOUND MINERAL SPRING AND APPROXIMATE LOCATION OF HARTVEY'S HOUSE (4 OLD APPLE TREES AND OLD CANS) CALLED OUT AT 39.42 CHS. AND 47.50 CHS. IN ORIGINAL NOTES. CORNER FALLS NEAR OLD WAGON ROAD BETWEEN OLD HIGHWAY AND NEW HIGHWAY. CONSIDERATION WAS GIVEN TO A 1/2" I.D. PIPE SET FROM CALLS PER 5 P.M. 1966, BUT MY CONCLUSIONS ARE THAT THE CALLS DO NOT FIT THE PIPE. I DETERMINED THE CORNER LOST AND SET A 2 1/2" x 30" ACAP AT THE SINGLE PRORATE POSITION, STAMPED AS SHOWN.
F.W.B.: 8" 4. PINE N33°E 25.1 FT. Mkd. "1/4 S23 BT" (NEW)
15" FORKED B. OAK N29°W 33.3 FT. Mkd. "1/4 S22 BT" (NEW)
1/2" I.D. IRON PIPE, NO TAG, N00°46'45"W 105.17 FT.

⑧ C-W-NW-SW
1/256
523
LS 49716
1986

SET: 2 1/2" x 30" ACAP. CORNER FALLS IN DRIVEWAY BURIED 3" BELOW GROUND STAMPED AS SHOWN.
F.W.B.: 14" D. FIR N34°W 25.1 FT. Mkd. "CWNWSW 1/256 S23 BT"
18" D. FIR S43°W 35.3 FT. Mkd. "CWNWSW 1/256 S23 BT"

⑨ C-E-NW-SW
1/256
523
LS 49716
1986

SET: 2 1/2" x 30" ACAP IN M.O.S. STAMPED AS SHOWN.
F.W.B.: 16" 4. PINE N20°W 19.7 FT. Mkd. "1/256 S23 BT"
12" 4. PINE N 82°E 61.2 FT. Mkd. "1/256 S23 BT"

⑩ SE-NW-SW
1/256
523
LS 49716
1986

SET: 2 1/2" x 30" ACAP IN M.O.S. STAMPED AS SHOWN.
F.W.B.: 18" 4. PINE N73°W 6.3 FT. Mkd. "1/256 S23 BT"
5" D. FIR N8°W 22.3 FT. Mkd. "X" "BT"

⑪ C-S-N-SW
1/256
523
LS 49716
1986

SET: 2 1/2" x 30" ACAP IN M.O.S. STAMPED AS SHOWN.
F.W.B.: 9" D. FIR N76°E 5.6 FT. Mkd. "1/256 S23 BT"
8" D. FIR S32°E 4.0 FT. Mkd. "1/256 S23 BT"

⑫ SW 1/16
523
LS 49716
1986

SET: 2 1/2" x 30" ACAP IN M.O.S. STAMPED AS SHOWN. CORNER FALLS ON NORTH EDGE OF OLD HIGHWAY.
F.W.B.: 9" 4. PINE S56°E 52.2 FT. Mkd. "SW 1/16 S23 BT"
10" D. FIR S42°W 52.0 FT. Mkd. "SW 1/16 S23 BT"

⑬ C-W-E-SW
1/256
523
LS 49716
1986

SET: 2 1/2" x 30" ACAP IN M.O.S. STAMPED AS SHOWN. CORNER FALLS UNDER POWER LINE.
F.W.B.: 12" CEDAR S62°E 16.3 FT. Mkd. "1/256 S23 BT"
11" D. FIR S26°W 30.0 FT. Mkd. "1/256 S23 BT"

⑭ NW-SE-SW
1/256
523
LS 49716
1986

SET: 2 1/2" x 30" ACAP IN M.O.S. STAMPED AS SHOWN. CORNER FALLS IN WET AREA WEST OF MASSACK REST AREA RESTROOMS.
F.W.B.: 12" COTTON WOOD S26°E 4.2 FT. Mkd. "1/256 S23 BT"
23" QUAD TRUNKED APPLE TREE WITH STOVE IN THE MIDDLE OF THE TRUNKS N44°E 21.1 FT. Mkd. "1/256 S23 BT"

⑮ C-W-SE-SW
1/256
523
LS 49716
1986

SET: 2 1/2" x 30" ACAP IN M.O.S. STAMPED AS SHOWN. CORNER FALLS ± 5' WEST OF ROAD TO U.P.R.R. TRACKS.
F.W.B.: 6" D. FIR S87°W 7.7 FT. Mkd. "X" "BT"
7" D. FIR S36°W 10.0 FT. Mkd. "1/256 S23 BT"

⑯ SW 1/4
523
64 276
LS 49716
1986

SET: 2 1/2" x 30" ACAP IN M.O.S. STAMPED AS SHOWN.
F.W.B.: 8" W. FIR N75°E 29.8 FT. Mkd. "1/64 S23 BT"
11" 4. PINE S36°E 8.1 FT. Mkd. "1/64 S26 BT"

⑰ W-EW 1/2
523
64 276
LS 49716
1986

SET: 2 1/2" x 30" ACAP IN M.O.S. STAMPED AS SHOWN.
F.W.B.: 9" W. FIR N5°W 29.6 FT. Mkd. "1/256 S23 BT"
17" W. FIR S54°W 18.3 FT. Mkd. "1/256 S26 BT"

⑱ SW-SE-SW
1/256
523
LS 49716
1986

SET: 2 1/2" x 30" ACAP IN M.O.S. STAMPED AS SHOWN.
F.W.B.: 11" D. FIR S46°W 8.3 FT. Mkd. "1/256 S23 BT"
12" D. FIR S89°W 10.8 FT. Mkd. "1/256 S23 BT"

⑲ C-S-S-SW
1/256
523
LS 49716
1986

SET: 2 1/2" x 30" ACAP IN M.O.S. STAMPED AS SHOWN.
F.W.B.: 18" CEDAR S89°W 23.9 FT. Mkd. "1/256 S23 BT"
9" 4. PINE N5°W 9.7 FT. Mkd. "1/256 S23 BT"

⑳ C-S-SW
1/164
523
LS 49716
1986

SET: 2 1/2" x 30" ACAP IN M.O.S. STAMPED AS SHOWN.
F.W.B.: 9" W. FIR N64°W 4.0 FT. Mkd. "1/64 S23 BT"
16" W. FIR S4°E 7.7 FT. Mkd. "1/64 S23 BT"

㉑ C-E-SW-SW
1/256
523
LS 49716
1986

SET: 2 1/2" x 30" ACAP IN M.O.S. STAMPED AS SHOWN.
F.W.B.: 14" CEDAR S22°E 21.2 FT. Mkd. "1/256 S23 BT"
5" W. FIR S58°W 18.4 FT. Mkd. "X" "BT"

㉒ NE-SW-SW
1/256
523
LS 49716
1986

SET: 2 1/2" x 30" ACAP IN M.O.S. STAMPED AS SHOWN.
F.W.B.: 9" D. FIR S80°W 13.1 FT. Mkd. "1/256 S23 BT"
9" W. FIR N28°W 17.1 FT. Mkd. "1/256 S23 BT"

㉓ C-N-SW-SW
1/256
523
LS 49716
1986

SET: 2 1/2" x 30" ACAP IN M.O.S. STAMPED AS SHOWN.
F.W.B.: 8" W. FIR N86°W 18.6 FT. Mkd. "1/256 S23 BT"
10" CEDAR S16°E 12.1 FT. Mkd. "1/256 S23 BT"

㉔ C-W-SW
1/164
523
LS 49716
1986

SET: 2 1/2" x 30" ACAP IN M.O.S. STAMPED AS SHOWN.
F.W.B.: 8" D. FIR N29°W 17.1 FT. Mkd. "1/64 S23 BT"
5" D. FIR S73°W 6.6 FT. Mkd. "X" "BT"

㉕ C-S-NW-SW
1/256
523
LS 49716
1986

SET: 2 1/2" x 30" ACAP IN M.O.S. STAMPED AS SHOWN.
F.W.B.: 13" 4. PINE N75°E 12.2 FT. Mkd. "1/256 S23 BT"
12" 4. PINE S17°W 50.3 FT. Mkd. "1/256 S23 BT"

㉖ SW-NW-SW
1/256
523
LS 49716
1986

SET: 2 1/2" x 30" ACAP IN M.O.S. STAMPED AS SHOWN.
F.W.B.: 10" D. FIR N73°E 12.9 FT. Mkd. "SWNWWSW 1/256 S23 BT"
6" D. FIR N22°W 10.2 FT. Mkd. "X" "BT"

RECORD OF SURVEY

FOR

VERNON FLETCHER AND THE U.S.D.A. - PLUMAS NATIONAL FOREST

MARK D. FILSINGER LAND SURVEYOR

473 BELL LANE QUINCY, CALIF. 95971

P.O. BOX 3108 (916) 283-0754