



**LEGEND**

- Set 1/2" rebar RCE 22836
- Fd. 8" concrete LS 3536 no record except as noted
- ⊗ Fd. monument as noted
- [ ] GLO Record

FSAP - Forest Service Aluminum Monument

- ① Section corner: 14-13-23-24  
GLO: post and mound  
Fd: tag LS 3536 in concrete 8" round (No record) and 4x4 post w/ 1940 K-tag in fence line. No trees convenient to mark.
- ② 1/4 corner 13-24  
GLO: Post and Mound  
Fd: tag LS 3536 in concrete 8" round (No record) Accepted for 1/4 corner. No trees convenient to mark.
- ③ SECTION CORNER 13-24 ONLY  
RECORD (R-1) FSAP  
Fd: FSAP  
24" PINE N54°W 131.68'  
17" PINE N36°E 275.4'
- ④ 1/4 CORNER S24 ONLY  
GLO: 19"x11"x5" stone  
Fd: 19"x11"x5" stone in MOR and STEEL FENCE POST  
SET 1/2" BAR RLE 22836  
NO TREES CONVENIENT TO MARK
- ⑤ 1/4 SECTION 23-24  
GLO: Post in MOUND  
Fd: tag LS 3536 in concrete 8" round (No Record) as. u.c. To INTERSECTION OF TWO FENCES. ACCEPTED AS BEST EVIDENCE OF CORNER. NO TREES CONVENIENT TO MARK
- ⑥ SECTION CORNER 23-24-25-26  
GLO: Post AND MOUND  
Fd: NEW FENCE RUNNING EAST-WEST IS 20' NORTH  
SET: 1/2" rebar in concrete RCE 22836  
CORNER SET BY DOUBLE PROPORTION BETWEEN TABBED 1/4 CORNERS ACCEPTED FOR THIS SURVEY.
- ⑦ 1/4 CORNER SECTION 24-25  
GLO: Post in MOUND  
Fd: tag LS 3536 in concrete 8" round Accepted as 1/4 CORNER PER 7.R.5.38  
NO TREES CONVENIENT TO MARK
- ⑧ SECTION CORNER 24-25 ONLY  
GLO: Post in MOUND  
RECORD: 8" concrete monument LS 3536 PER 7.R.5.32  
Fd: tag LS 3536 in concrete 8" round  
32" PINE N45°E 433.36'  
16" PINE N27°E 466.6'
- ⑨ 1/4 CORNER SECTION 25-26  
RECORD: Concrete monument LS 3536 PER 7.R.5.38  
Fd: tag LS 3536 in concrete 8" round  
No trees convenient to mark.
- ⑩ 1/4 CORNER SECTION 23-26  
GLO: Post in MOUND  
Fd: tag LS 3536 in concrete 8" round (No record) Accepted as best evidence of corner. No trees convenient to mark.
- ⑪ SECTION CORNER 22-23-26-27  
GLO: Post in MOUND  
Fd: NEW FENCE RUNNING NORTH-SOUTH  
SET: 1/2" bar RLE 22836 w/ single proportion on EAST-WEST LINE ONLY.  
NOT TRUE SECTION CORNER
- ⑫ 1/4 CORNER SECTION 22-27  
GLO: Post in MOUND  
Fd: 4x4 post 3' south of fence line and 20't NORTH of SURVEY LINE, WORN BY CATTLE TO 2' HIGH.  
NOT ACCEPTED AS ORIGINAL CORNER. SET tag RCE 22836 on post for future surveys.  
NO TREES CONVENIENT TO MARK.
- ⑬ SECTION CORNER 21-22-27-28  
GLO: Post in MOR  
Fd: 4x4 post w/ scribes in MOR and 1/2" bar LS 2843.  
NO TREES CONVENIENT TO MARK.

**RECORD OF SURVEY**

— for —  
**KARL TAYLOR et al**

A portion of Section 24 T23N R16E MDBM near Chilcoat, Plumas County, California

Clifford R. Brown Engineering & Survey  
Rt. 1 Box 480B  
Quincy, Calif. 283-3959