

<p>T26N R9E S_{1/16} S26 S25 LS 5287 1984</p> <p>CORNER No. 1 FD. A STD USFS MON IN A MOUND OF STONE PER (1). CORNER FALLS ON A MODERATE EAST SLOPE AT THE TOE OF FILL OF BACKHOE YARD. FD. A 20" DOUGLAS FIR, S36W, 12.4' -HB REC. A 14" DOUGLAS FIR, S35'57"E, 12.4' (1)</p>	<p>T26N R9E R10E S25 S30 S36 S31 1970 BLM</p> <p>CORNER No. 9 FD. A BLM STEEL CAP ON A 3" PIPE PER (2). CORNER FALLS ON A NORTH SLOPE IN THICK TIMBER, 200'± SOUTH OF A DIRT ROAD. FD. A 19" FIR SNAG, S64W, 4.0' -HB REC. A 24" FIR SNAG, S66W, 6 LKS (BLM) FD. AN 18" WHITE FIR, S66E, 24.4' -HB REC. A 4" FIR, S66E, 37 LKS (BLM)</p>	<p>CORNER NOTES</p> <p>HB = HEALED BLAZE VS = VISIBLE SCRIBING STD USFS MON = A 3 1/4" ALUM. CAP ON A 2 1/2" ALUM. PIPE (1) = RECORD PER 7 RS 33 (2) = RECORD PER 4 RS 61 (3) = RECORD PER UNRECORDED SURVEY BY CRANNER ENGINEERING FOR THE CHY Co. DATED AUGUST, 2003 (4) = RECORD PER 7 RS 97 ALL ACCESSORIES MEASURED TO FACE</p>		
<p>CORNER No. 2 SET A 5/8" REBAR WITH 2" ALUM. CAP FOR A 25.0' WITNESS CORNER ON THE LINE TO THE WEST. TRUE CORNER FALLS NEXT TO THE BACK STEPS OF A HOUSE. NO ACCESSORIES TAKEN</p>				
<p>T26N R9E WC S26 S25 S35 S36 LS 5287 1984</p> <p>FD. AN 8" SUGAR PINE, S52W, 28.1' -VS REC. A 7" SUGAR PINE, S25E, 19.5' (1) FD. A 17" DOUGLAS FIR, S25E, 19.5' -HB REC. A 15" DOUGLAS FIR, S52W, 28.1' (1)</p>				
<p>WC T26N R9E S26 S25 S35 S36 LS 5287 1984</p> <p>CORNER No. 3B FD. A STD USFS MON IN A MOUND OF STONE PER (1). CORNER FALLS ON A STEEP NORTH SLOPE IN SCATTERED TIMBER, 300'± SOUTH OF THE RIVER. FD. AN 8" DOUGLAS FIR, S9W, 27.6' -HB REC. A 5" DOUGLAS FIR, S9W, 27.6' (1) FD. A 13" DOUGLAS FIR SNAG, N50W, 31.2' -HB REC. AN 11" DOUGLAS FIR, N50W, 31.2' (1)</p>				
<p>CORNER No. 4 SEE DETAIL ON SHEET 1.</p>				
<p>T26N R9E 1/4 S25 S26 LS 5287 1984</p> <p>CORNER No. 5 FD. A STD USFS MON IN A MOUND OF STONE PER (1). CORNER FALLS ON A STEEP NORTHEAST SLOPE IN HEAVY TIMBER. FD. A 27" DOUGLAS FIR, S50E, 39.8' -HB REC. A 22" DOUGLAS FIR, S50E, 39.8' (1) FD. A ±60" DOUGLAS FIR, N87W, 91.3' REC. A 50" DOUGLAS FIR, N86'48"W, 91.3' (1)</p>				<p>RECORD OF SURVEY FOR W M BEATY & ASSOCIATES "WHEELOCK"</p>
<p>RCE 13309</p> <p>CORNER No. 6 FD. A CAP MARKED RCE 13309 ON A REBAR PER (3). ACCEPTED AS N 1/16 35 36. NO ACCESSORIES FOUND, NONE TAKEN</p>				<p>IN SECTIONS 25 AND 36, T 26 N, R 9 E, MDM, IN THE UNINCORPORATED AREA OF PLUMAS COUNTY, STATE OF CALIFORNIA</p>
<p>RCE 13309</p> <p>CORNER No. 7 FD. A CAP MARKED RCE 13309 ON A REBAR PER (3). ACCEPTED AS NW 1/16 SEC 36. NO ACCESSORIES FOUND, NONE TAKEN</p>				<p>DEL TERRA INC. SURVEYING 1168 INDUSTRIAL ST. REDDING, CA 96002 PHONE (530) 241-8050</p> <p>DATE: JUNE, 2004 SHEET 2 OF 2</p>