

SECTION 1

- ① SW COR SEC 1
 RECORD: 3/4 IP LS 2322 (R1)
 FWBS:
 40" FIR N 70°W 54.8'
 35" FIR N 65°E 2.6'
 32" FIR S 15°E 18.5'
 FOUND: FD STANDARD BLM MONUMENT (1975)(R2)
 REPLACED (R1) CORNER
 FWBS:
 16" PINE S41°27'W 43.5' (R2)
 GRANITE BOULD. 8X10X6 N58°02'W 12.4' (R2)
 32" SNAG ORIG. BT S13°21'E 17.5' (R1)
 SET: NOTHING
- ② S 1/4 COR SEC 1
 RECORD: 4" RR RAIL IN M.O.S. (R1)
 FWBS:
 24" W FIR S 33°W 191.0'
 23" LODGEPOLE S 12°E 234.0'
 FOUND: STANDARD BLM MON. (1975) (R2)
 (BLM MON REPLACES R1 MONUMENT)
 FWBS:
 36" W FIR S 33°W 190.7'
 30" LODGEPOLE S12°E 233.6'
 SET: NOTHING
- ③ W 1/4 COR SEC 1
 RECORD: 5/8" ROD WITH 2 1/2" CAP LS 2322 (R1)
 FWBS:
 37" LODGEPOLE S70°W 104'
 FOUND: STANDARD BLM MONUMENT (R2)(1982)
 FWBS:
 37" LODGEPOLE STUMP S71°30'W 103.6'
 21" TAMARACK N 87°E 70.6' (R2)
 22" TAMARACK N85°W 33.7' (R2)
 SET: NOTHING
- ④ NW COR SEC 1
 RECORD: 5/8" ROD WITH 2 1/2" CAP LS 2322 (R1)
 FWBS:
 10" LODGEPOLE N 58°W 22.0'
 12" LODGEPOLE N 33°E 21.0'
 FOUND: 5/8" ROD WITH 2 1/2" CAP LS 2322 (R1)
 FWBS:
 20" LODGEPOLE N 58°W 22.0'
 18" LODGEPOLE N 33°E 21.0'
 SET: NOTHING
- ⑤ NE COR SEC 1
 RECORD: 1" PIPE LS 3202 (R1)
 FWBS:
 Y PINE STUMP N 86°E 90.4'
 Y PINE STUMP S 27°E 55.4'
 Y PINE STUMP S 60°W 144.5'
 FOUND: 1" IP LS3202 (R1)
 FWBS:
 Y PINE STUMP N 86°E 90.4'
 Y PINE STUMP S 27°E 55.4'
 Y PINE STUMP S 60°W 144.5'
 SET: REPLACED 1"IP (R1) W/ STANDARD USFS MON.
 FWBS:
 60"Y PINE S 59°01'W 197.5' NBT

- ⑥ S 1/16 W COR SEC 1
 RECORD: 5/8" ROD WITH 2 1/2" CAP LS 2322 (R1)
 FWBS:
 10" W FIR S 51°W 16.5'
 8" Y PINE N 17°E 28.1'
 FOUND: 5/8" ROD WITH 2 1/2" CAP LS 2322 (ACCEPTED)
 FWBS:
 1"IP LS 4643 N 18°54' W 4.4' (NO REC.)
 20" P PINE WTAG N 16°18' E 28.3'
 SET: REPLACED (R1) W/ STANDARD USFS MON
 FWBS:
 12" FIR NBT S 16°22' W 16.0'
 20" P PINE N 16°18' E 28.3'
- ⑦ SW 1/16 COR SEC 1
 RECORD: NONE
 FOUND: NOTHING
 SET: STANDARD USFS MON
 FWBS:
 11" TAMARACK NBT S 77°18' E 70.0'
 12" TAMARACK NBT N 53°46' W 55.1'
- ⑧ W 1/16 S COR SEC 1
 RECORD: NONE
 FOUND: NOTHING
 SET: STANDARD USFS MON
 FWBS:
 16" FIR NBT S 6°54' E 42.9'
 11" FIR NBT S 75°49' E 18.4'

SECTION 12

- ⑨ E 1/4 COR SEC 12
 RECORD: 3/4" PIPE LS 2322 IN STONE MOUND (R1)
 FWBS:
 66" W FIR S 84°W 18.5'
 42" W FIR N 22°E 29.0'
 FOUND: STANDARD BLM MON (1975) (R2)
 (REPLACED (R1) MONUMENT)
 FWBS:
 57" W FIR SNAG S 88°W 20.4'
 45" W FIR N 18°E 27.7'
 18" FIR N32°W 45.5' (R2)
 SET: NOTHING

SECTION 31

- ⑩ N 1/4 COR S31
 RECORD: STANDARD U.S.D.A. BRASS CAP (R4)
 FWBS:
 9" W FIR S 10°W 28.4'
 8" Y PINE S 25°E 16.0'
 FOUND: NOTHING AT CORNER POSITION
 SET: STANDARD U.S.F.S. MONUMENT
 FWBS:
 11" FIR NBT N 8°06'17" E 12.1'
 14" S PINE NBT S 3°24'30" E 22.5'
 STANDARD U.S.F.S. MON N73°29'22"E 38.16
 (CORNER WAS SET INCORRECTLY AS PER 4RS148)

- ⑪ C 1/4 COR S31
 RECORD: 5/8" ROD W/ 1.5" CAP L.S.3621 (R4)
 FWBS:
 6" W FIR N 75°W 31.3'
 10" W FIR N 36°E 18.3'
 FOUND: NOTHING AT CORNER POSITION
 SET: STANDARD U.S.F.S. MONUMENT
 FWBS:
 9" IN CEDAR NBT N30°06'25"E 41.7'
 11" IN CEDAR NBT N50°45'27"W 21.7'
 1.5" IN ALMCAP S72°25'18"E 23.60'
- ⑫ CW 1/16 COR S31
 RECORD: 5/8" ROD W/ 1.5" CAP L.S.3621 (R4)
 FWBS:
 8" D.FIR S 79°W 31.8'
 FOUND: NOTHING
 SET: STANDARD U.S.F.S. MONUMENT
 FWB:
 11" IN FIR NBT N84°53'12"E 21.0'
 11" IN CEDAR NBT S42°27'00"E 26.0'
 5/8" ROD W/ 1.5" CAP L.S.3621
 S73°58'22"E 12.63' (NOT ACCEPTED
 DUE TO THE DEFECTIVE N 1/4 COR)
- ⑬ W 1/16 S COR S31
 RECORD: 5/8" ROD W/ 1.5" CAP L.S.3621 (R4)
 FWBS:
 6" W.FIR N38°E 19.9'
 FOUND: 5/8" ROD W/ 1.5" CAP L.S.3621 (ACCEPTED)
 FWBS:
 12" FIR BT W/TAG N 33°41' E 19.6'
 SET: NOTHING
- ⑭ NW COR S31
 RECORD: U.S.F.S. ALUMINUM PIPE/CAP (R4)
 FWBS:
 9" W FIR N67°E 13.2'
 FOUND: U.S.F.S. ALUMINUM PIPE/CAP (ACCEPTED)
 SET: NOTHING

SURVEY HISTORY

- (R1) 4RS6&7 (LS 2322)
- (R2) BLM REMON. (1975)
- (R3) 6RS48 (LS 3318)
- (R4) 4RS148 (LS 3621)

- ⑮ E 1/4 COR S31
 RECORD: U.S.F.S. ALUMINUM PIPE/CAP (R4)
 FWBS:
 5" W.FIR N70° E 47.8'
 5" W FIR S47° W 34.3'
 FOUND: U.S.F.S. ALUM. PIPE/CAP (ACCEPTED)
 SET: NOTHING
- ⑯ SW COR S31
 RECORD: 1" I.P. LS 3202 (R4)
 FWBS:
 STANDARD USDA BRASS CAP W.C.
 (SET NORTH 4.0')
 24" W FIR N 15°E 26.1"
 24" R FIR S 35°E 15.2"
 22" Y PINE N 70°W 75.2"
 22" R FIR S 40°W 13.2"
 FOUND: 1" IP LS 3202 (R4)
 FWBS:
 USFS ALUM. PIPE/CAP(W.C. 4.0' NOR.)
 32" W FIR N 15°E 26.1"
 30" R FIR S 35°E 15.2"
 33" Y PINE N 70°W 75.2"
 31" R FIR S 40°W 13.2"
- ⑰ S 1/4 COR S31
 RECORD: USFS ALUMINUM PIPE/CAP (R4)
 FWBS:
 9" W FIR N 48°W 12.4'
 10" W FIR S 32°W 26.6'
 FOUND: USFS ALUMINUM PIPE/CAP (R4)
 FWBS:
 18" W FIR N 48°W 12.4'
 21" W FIR S 32°W 26.6'
 SET: NOTHING
- ⑱ W 1/4 COR S31
 RECORD: 2" IRON PIPE W/ BRASS CAP LS 3621 (R4)
 FWBS:
 7" S PINE S 68°W 27.0'
 13" CEDAR S 69°E 25.2'
 9" CEDAR S 5°E 20.7'
 FOUND: STANDARD USFS MON. LS 3621 (R4)
 FWBS:
 15" S PINE S 68°W 27.0'
 17" CEDAR S 69°E 25.2'
 20" CEDAR S 5°E 20.7'
 SET: NOTHING

RECORD OF SURVEY
 SECTION 1, T26N R6E & SECTION 31, T27NR6E MDM,
 PLUMAS COUNTY, CALIFORNIA
 FOR
 U.S.D.A. LASSEN NATIONAL FOREST
 2550 RIVERSIDE DRIVE
 SUSANVILLE, CA 96130
 DRAWN BY: B. SNOW DATE: DECEMBER, 2006
 SHEET 3 OF 3