

Section 14

1 NW S14
RECORD: (R1) SET 16"x13"x11" STONE BY M.O.S.
FOUND: 4" RAILROAD RAIL (SET BY CAF.)
ACCEPTED AS BEST EVIDENCE OF THE ORIGINAL GLO CORNER.
SET: STANDARD U.S.F.S. MONUMENT (REPLACED FD COR)

2 N 1/4 S14
RECORD: (R1) SET STONE 14"x10"x9"
FWB: 22"S.PINE S14"W, 31LKS. ; 10"FIR N6"E,50LKS.
FOUND: 1" OPEN IRON PIPE ACCEPTED AS BEST EVIDENCE OF ORIGINAL CORNER

3 NE S14
RECORD: (R1) STONE 20"x18"x15"
FOUND: COLLINS ALMANOR FOREST MONUMENT
ACCEPTED AS BEST EVIDENCE OF ORIG. CORNER

4 W 1/4 S14
RECORD: (R1) STONE 18"x14"x6"
FOUND: MOUND OF STONE ACCEPTED AS BEST EVIDENCE OF ORIG. CORNER.
SET: STANDARD U.S.F.S. MONUMENT

5 E 1/4 S14
RECORD: (R1) STONE 16"x10"x9"
FWBS: 32"S.PINE N59"E,42 LKS.-37"FIR N65I/2"W, 73 LKS.
FOUND: 3/4"OPEN IRON PIPE IN M.O.S., ACCEPTED AS BEST EVIDENCE OF ORIG. CORNER

6 S 1/16 S15\14
RECORD: NONE
FOUND: NOTHING
SET: STANDARD U.S.F.S. MONUMENT

7 SW 1/16 S14
RECORD: NONE
FOUND: NOTHING
SET: STANDARD U.S.F.S. MONUMENT

8 SW S14
RECORD: (R1) STONE 14"x13"x12"
FOUND: CAF. MONUMENT ACCEPTED

9 W 1/16 S14/S23
RECORD: NONE
FOUND: NOTHING
SET: STANDARD U.S.F.S. MONUMENT

10 S 1/4 S14
RECORD: (R1) STONE 20"x14"x9"
FOUND: MARKED STONE 20"x14"x9" IN M.O.S.
SET: REPLACED W/STANDARD U.S.F.S. MONUMENT

11 N 1/4 S15
RECORD: (R1) PITS & MOUNDS (CORNER LOST IN LAKE)
ESTABLISHED COR. POINT AT (R1) BEARING AND DISTANCE FROM THE NE CORNER SEC 15. (GLO JM INGALLS 1860)

12 W 1/4 S15
RECORD: (R1) POST (CORNER LOST IN LAKE)
ESTABLISHED COR. POINT AT (R1) BEARING AND DISTANCE FROM CALC. SW S15

13 C 1/4 S15
SET: STANDARD U.S.F.S. MONUMENT
FWB 8" CEDAR S22*26'E 432'
FWB 13" CEDAR N84*10'E 666'

14 SW S15
RECORD: (R1) POST (CORNER LOST IN LAKE)
ESTABLISHED CORNER POINT BY A (THREE POINT CONTROL) PRORATED POSITION.

15 S 1/4 S15
RECORD: (R1) 8" FIR CORNER TREE
FOUND: 26" CORNER TREE (CLOSED FACES), ACCEPTED

16 W 1/4 S22
RECORD: (R1) MARKED 15" P.PINE
ESTABLISHED AT A PROPORTIONED POSITION (CORNER FALLS IN THE LAKE)

17 CW 1/16 S22
RECORD: NONE
FOUND: NOTHING
SET: STANDARD U.S.F.S. MONUMENT

18 C 1/4 S22
RECORD: NONE
FOUND: NOTHING
SET: STANDARD U.S.F.S. MONUMENT

19 E 1/4 S22
RECORD: (R1) POST
FOUND: CAF. MONUMENT ACCEPTED CORNER

20 SW S22
RECORD: (R2)- STONE 18"x8"x5"
FOUND: STANDARD USFS MONUMENT (UNRECORDED) A REMONUMENTATION OF ORIGINAL CORNER (R2)

21 W 1/16 S22/S27
RECORD: AN UNRECORDED USFS MONUMENT.
FOUND: STANDARD U.S.F.S. MONUMENT (UNRECORDED)

22 S1/4 S22
RECORD: (R2)- LAVA STONE 18"x10"x8"
FOUND: STANDARD U.S.F.S. MONUMENT (UNRECORDED)

23 SE S22
RECORD: (R2) LAVA STONE 12"x12"x7"
FOUND: CAF MONUMENT ACCEPTED CORNER

24 NW 28
RECORD: (R2) LAVA STONE 12"x7"x7"
FOUND: 4" RR RAIL ACCEPTED CORNER (CALTRANS)

25 N 1/4
RECORD: (R2) MKD. POPULAR TREE FOR WITNESS CORNER.
SET: PROPORTIONED POSITION.(FALLS IN LAKE)

26 NE 1/16 S28
RECORD: NONE
FOUND: NOTHING
SET: STANDARD U.S.F.S. MONUMENT

27 N 1/16 S28\S27
RECORD: NONE
FOUND: NOTHING
SET: STANDARD U.S.F.S. MONUMENT

28 W 1/4 S28
RECORD: (R2) 14"x10"x7" STONE
FWB: 36" CEDAR S69*40'E 103 LKS
FWB: 58" FIR N47*20'W 107 LKS
FOUND: (R2) 14"x10"x7" MKD STONE ACCEPTED

29 CE 1/16 S28
RECORD:
FOUND: NOTHING
FWB: 1" OPEN IP S47*10'W 21.37'

30 E 1/4 S28
RECORD: (R2) LAVA STONE 16"x10"x8"
FOUND: STANDARD U.S.F.S. MON. (USFS SURVEY IN PROGRESS) ACCEPTED

31 S 1/4 S28
RECORD: (R2) STONE 17"x10"x4"
FWBS: 16" FIR N72"W, 29.5'
FOUND: 17"x10"x5" STONE, ACCEPTED CORNER
FWB: ORIG DOWNED SCRIBED FIR N75*52'W 29.5'

32 E 1/16 S28\S33
RECORD: NONE
FOUND: NOTHING
SET: STANDARD U.S.F.S. MONUMENT

33 SE S28
RECORD: (R2) GLO 14"x8"x6" LAVA STONE
FOUND: FOUND ORIGINAL MARKED STONE IN MOS, ACCEPTED

28|27|33
FWB: 38" STUMP WITH SCRIBING N58*13' E 12.9'
(R2) 18" FIR N60*22'E 19.1'
FWB: 27" P PINE N45*56'W 29.1'
(R2) 20" PINE N45*30'W 30.03'
FWB: 44" S PINE 1940 BRC TAG S67*34'W 23.1'

LEGEND

- FWB FROM WHICH BEARS
GLO GENERAL LAND OFFICE
ALM ALUMINUM
P.PINE PONDEROSA PINE
S.PINE SUGAR PINE
BT BEARING TREE
RM REFERENCE MONUMENT
USFS U.S.FOREST SERVICE
CAF. COLLINS ALMANOR FOREST
MOS MOUND OF STONE
R1 J.M.INGALLS (GLO 1860)
R2 V. BARBER (GLO 1904)

Section 22

16 W 1/4 S22
RECORD: (R1) MARKED 15" P.PINE
ESTABLISHED AT A PROPORTIONED POSITION (CORNER FALLS IN THE LAKE)

17 CW 1/16 S22
RECORD: NONE
FOUND: NOTHING
SET: STANDARD U.S.F.S. MONUMENT

Section 28

24 NW 28
RECORD: (R2) LAVA STONE 12"x7"x7"
FOUND: 4" RR RAIL ACCEPTED CORNER (CALTRANS)
WITH ORIG. FACE AND SCRIBING (WRONG QUAD.) (R2 40" FIR N33*30'E 80LKS)

25 N 1/4
RECORD: (R2) MKD. POPULAR TREE FOR WITNESS CORNER.
SET: PROPORTIONED POSITION.(FALLS IN LAKE)

RECORD OF SURVEY
CORNER NOTES FOR SECTIONS 14,15,22,28; T27NR8E MDM
PLUMAS COUNTY, CALIFORNIA
FOR
U.S.D.A. PLUMAS NATIONAL FOREST
P.O.BOX 11500, QUINCY, CA. 96971
DRAWN BY: B.SNOW DATE: OCTOBER 2006 SHT 5 OF 5