

27 LENA NO THIRTEEN COR 3
 RECORD: 6'X6'X3.5' SPRUCE POST IN M.O.S.
 FWB: 16'FIR N80°15'E 14.0'
 FWB: 16'FIR S26°45'W 23.5'
 FOUND: M.O.S. W/T-POST (ACCEPTED AS CORNER)
 FWB: 26'FIR STUMP W/FACE N82°19'E 15.4' OBT
 SET: STANDARD USFS MONUMENT
 FWB: 12' PINE N26°49'E 17.9' NBT
 FWB: 12' CEDAR N87°05'W 11.8' NBT

28 LENA NO THIRTEEN COR NO 2-2
 RECORD: 4'X4'X3.5' FIR POST
 FWB: 28'FIR S65°45'W 80.0'
 FWB: 16'FIR S68°30'E 73.8'
 FOUND: M.O.S. W/T-POST (ACCEPTED AS CORNER)
 FWB: 40'FIR SNAG S65°50'W 75.3' OBT
 FWB: 31'FIR SNAG S70°00'E 73.5' OBT
 SET: STANDARD USFS MONUMENT
 FWB: 18'FIR N18°12'W 21.8' NBT
 FWB: 12'FIR N34°34'E 31.1' NBT

29 LENAN NO TWELVE COR 3-1
 RECORD: 6'X6'X3.5' SPRUCE POST
 FWB: 20'PINE S62°15'W 19.3'
 FWB: 10'SPRUCE N3°00'E 25.0'
 FOUND: M.O.S. W/POST (ACCEPTED AS CORNER)
 SET: STANDARD USFS MONUMENT
 FWB: 11'PINE N10°38'W 17.4' NBT
 FWB: 18'PINE S43°43'W 70.1' NBT

30 LENA NO TWELVE COR 4
 RECORD: 6'X6'X3.5' FIR POST
 FWB: 16'FIR N22°00'W 19.7'
 FWB: 24'FIR S12°30'W 21.5'
 FOUND: M.O.S. W/T-POST (ACCEPTED AS CORNER)
 FWB: 30'FIR SNAG N20°00'E 20.00'
 FWB: 42'FIR S13°00'W 21.0'
 SET: STANDARD USFS MONUMENT
 FWB: 9'FIR S65°41'E 20.3 NBT
 FWB: 12'FIR S25°51'W 12.6' NBT

MS 5551

ALL RECORD IS FROM MS5551 - WILLIAM WATSON 1921

31 LENA EXT NO 2 LODE COR 2
 RECORD: 4'X4'X3.5' FIR POST
 FWB: 15'PINE S69°05'W 23.0'
 FWB: 24'FIR S3°15'W 15.1'
 FOUND: M.O.S. (ACCEPTED AS CORNER)
 FWB: 35'PINE S59°51'W 20.5' OBT
 SET: STANDARD U.S.F.S. MONUMENT
 FWB: 9'PINE N70°53'E 62.0' NBT
 FWB: 14'FIR S30°10'E 68.2' NBT

32 IRON DYKE FRACTION LODE COR 2
 RECORD: 4'X4'X 3.5' FIR POST
 FWB 36'FIR N67°35'W 34.8'
 FWB 9'PINE N47°22'E 39.9'
 FOUND: MOS./T-POST (ACCEPTED AS CORNER)
 FWB:18'PINE STUMP N47°10'E 39.6 '(SCRIBED)
 SET: STANDARD U.S.F.S. MONUMENT
 FWB 10'CEDAR N87°25'E 21.4' NBT
 FWB: 11'PINE S2°11'E 4.4' NBT

33 IRON DYKE LODE COR 3
 RECORD: 4'X4'X3.5' FIR POST
 FWB: 36'FIR S43°00'E 87.5'
 FWB: 9'FIR S60°00'W 35.1'
 FOUND: M.O.S. W/T-POST (ACCEPTED AS CORNER)
 FWB: 40'FIR STUMP S43°45'E 89.1 '(SCRIBING)
 FWB: 32'FIR CLOSED FACE S58°30'W 36.2'
 SET: STANDARD U.S.F.S. MONUMENT
 FWB: 14'FIR S87°25'E 109.4 NBT
 FWB: 12'FIR N4°19'E 20.4' NBT

34 IRON DYKE LODE COR 2
 RECORD: 4'X4'X3.5' FIR POST
 FWB: 11'PINE N27°00'W 15.7'
 FWB: 6'FIR N38°00'E 8.3'
 FOUND: M.O.S. W/T-POST (ACCEPTED AS CORNER)
 FWB: 23'PINE N29°16'W 15.3'
 FWB: 16'FIR N33°47'E 7.6' (CLOSED FACE)
 SET: STANDARD U.S.F.S. MONUMENT

35 IRON DYKE LODE COR 1
 RECORD: 4.5'X4.5'X 3.5' FIR POST
 FWB: 24'PINE S4°15'E 56.4'
 FWB: 26'PINE N53°45'E 38.5'
 FOUND: MOS./T-POST ACCEPT AS CORNER
 FWB: 35'DOWNED PINE SNAG S7°43'E 55.3'
 FWB: 38'PINE N51°14'E 37.5 '(CLOSED FACE)
 SET: W.C. STANDARD U.S.F.S. MON.
 FWB: 12'FIR N87°44'E 28.9' NBT TO WC
 FWB: 10'FIR S21°16'E 16.0' NBT TO WC
 FWB: TRUE COR. POINT BRS. S59°01'28"E 3.92'
 (TRUE CORNER POINT FALLS ON A BIG ROCK.)

MS 5582 A&B

ALL RECORD IS FROM MS5582 A&B WILLIAM WATSON 1921

36 PACIFIC NO 2 COR 1
 RECORD: 5'X5'X3.5' PINE POST
 FWB: 22'FIR S65°30'E 50.4'
 FWB: 16'FIR N79°15'E 109.5'
 FOUND: M.O.S. (ACCEPTED AS CORNER)
 FWB: 36'FIR N79°37'E 111.0' CLOSED FACE
 FWB: 27'FIR S66°06'E 51.6' CLOSED FACE
 SET: STANDARD U.S.F.S. MONUMENT
 FWB: 14'FIR N11°09'W 12.4' NBT

37 PACIFIC NO 2 COR 2
 RECORD: 4'X4'X 3.5' SPRUCE POST
 FWB: 18'PINE S19°30'W 33.4'
 FWB: 18'FIR N11°00'W 31.3'
 FOUND: MOS. (ACCEPTED AS CORNER)
 SET: STANDARD U.S.F.S. MONUMENT
 FWB: 9'FIR N7°12'E 20.8' NBT
 FWB: 15'PINE S36°54'W 14.2' NBT

38 PACIFIC NO 3 COR 3
 RECORD: 4'X4'X3.5' TAMARACK POST
 FWB: 10'TAMARACK N40°00'W 9.2'
 FWB: 12'TAMARACK S15°30'E 38.9'
 FOUND: M.O.S. (ACCEPTED AS CORNER)
 FWB: 15'TAMARACK ROTTEN STUMP N44°10'W 8.9'
 FWB: 19'TAMARACK S15°11'E 39.0' CLOSED FACE
 SET: STANDARD U.S.F.S. MONUMENT
 FWB: 11'TAMARACK N71°59'W 11.9' NBT

39 PACIFIC NO 4 COR 1
 RECORD: 4'X4'X3.5' TAMARACK POST
 FWB: 24'TAMARACK S71°00'W 16.0'
 FWB: 14'TAMARACK N32°00'W 33.7'
 FOUND: M.O.S. (ACCEPTED AS CORNER)
 FWB 24'TAMARACK N32°43'W 33.7'
 FWB 35'TAMARACK S69°36'W 16.0'
 SET: STANDARD U.S.F.S. MONUMENT
 FWB: 12'FIR N18°57'W 25.6' NBT

40 PACIFIC NO 4 COR 4
 RECORD: 4'X5'X 3.5' SPRUCE POST
 FWB: 30'FIR N14°30'E 33.6'
 FWB: 36'FIR N77°15'E 23.0'
 FOUND: MOS. (ACCEPT AS CORNER)
 FWB: 36'FIR STUMP N13°17'E 33.4 '(SCRIBING)
 FWB: 46'FIR STUMP N75°57'E 22.5 '(SCRIBING)
 SET: STANDARD U.S.F.S. MONUMENT
 FWB: 9'FIR N70°33'W 16.3' NBT
 FWB: 14'FIR S10°05'W 24.3' NBT

41 PACIFIC NO 5 COR 3
 RECORD: 4'X4'X3.5' SPRUCE POST
 FWB: 30'FIR N14°00'E 36.6'
 FWB: 20'FIR N30°30'W 56.4'
 FOUND: M.O.S. (ACCEPTED AS CORNER)
 FWB: 32'FIR N13°58'E 36.2'
 FWB: 33'FIR N29°40'W 56.5'
 SET: STANDARD U.S.F.S. MONUMENT
 FWB: 9'FIR N89°45'W 39.5' NBT
 FWB: 17'PINE N34°06'E 44.7' NBT

42 PACIFIC NO 6 COR 2
 RECORD: 4'X4'X3.5' FIR POST
 FWB: 58'PINE N32°45'E 92.0'
 FWB: 44'PINE S74°30'W 127.3'
 FOUND: M.O.S. (ACCEPTED AS CORNER)
 FWB: 60'PINE N34°19'E 91.1' SCRIBING
 FWB: 48'PINE STUMP S76°02'W 126.6'
 SET: STANDARD U.S.F.S. MONUMENT
 FWB: 13'FIR N11°18'E 12.6' NBT
 FWB: 9'FIR S47°20'W 23.0' NBT

SEC.7 T24NR12E MDM

43 1/1024 SEC 7
 RECORD: NONE
 FOUND: NOTHING
 SET: STANDARD U.S.F.S. MONUMENT
 FWB: 12'CEDAR N74°29'W 24.6' NBT
 FWB: 12'CEDAR S40°46'E 43.2' NBT

44 NE-NE-NE 1/256
 RECORD: NONE
 FOUND: NOTHING
 SET: STANDARD U.S.F.S. MONUMENT
 FWB: 12'FIR N27°50'E 47.0' NBT
 FWB: 15'FIR S66°35'W 53.6' NBT

45 E-E-E 1/256
 RECORD: NONE
 FOUND: NOTHING
 SET: STANDARD U.S.F.S. MONUMENT
 FWB: 18'PINE N32°46'E 11.9' NBT
 FWB: 14'FIR S52°58'W 36.5' NBT

LEGEND

- FWB FROM WHICH BEARS
- GLO GENERAL LAND OFFICE
- ALM ALUMINUM
- PINE PONDEROSA PINE
- FIR WHITE FIR
- (R1) M.S. SURVEYOR-WILLIAM WATSON 1921
- NBT NEW BEARING TREE
- RM REFERENCE MONUMENT
- USFS U.S. FOREST SERVICE
- MOS MOUND OF STONE

RECORD OF SURVEY
 CORNER NOTES: M.S.5551,5495,5582 A&B T24NR12E MDM,
 PLUMAS COUNTY, CALIFORNIA
 FOR
U.S.D.A. PLUMAS NATIONAL FOREST
 P.O.BOX 11500
 QUINCY, CA 95971
 DRAWN BY: B. SNOW DATE: DECEMBER, 2006