

<p>LS 4753</p> <p>CORNER No. 2 FD. A 2" CAP (STAMPED "LS 4753" BY THIS SURVEY) ON A 1" IRON PIPE IN A MOUND OF STONE. CORNER FALLS ON A STEEP NORTHWEST SLOPE, 75°± EAST OF A ROAD. FD. A 19" PONDEROSA PINE, S3°E, 31.0' NO REC. FD. A 28" DOUGLAS FIR, N84°E, 59.4' NO REC.</p>	<p>T26N R9E 1/4 S4 S9 S9 LS 4753 2008</p> <p>CORNER No. 8 NOTHING FD SET A USFS DRIVE IN MONUMENT IN A SMALL MOUND OF STONE. CORNER FALLS ON A STEEP NORTHEAST SLOPE, 100°± WEST OF A RAVINE. SCRIBED A 16" DOUGLAS FIR, S42°E, 35.9' "1/4 S9 BT" SCRIBED A 10" WHITE FIR, N1°E, 14.1' "1/4 S1 BT"</p>	<p>CORNER NOTES HB = HEALED BLAZE VS = VISIBLE SCRIBING BCIP = BRASS CAPPED IRON PIPE USFS DRIVE IN MON. = 3-1/4" ALUM CAP ON A 5/8" ALUM. ROD</p>	<p>NW 1/16 S10 LS 4753 2008</p> <p>CORNER No. 20 SET A USFS DRIVE IN MONUMENT ON A MOUND OF STONE. CORNER FALLS ON A STEEP SOUTH SLOPE IN CUTBANK OF OLD ROAD. SCRIBED A 7" DOUGLAS FIR, N54°W, 15.1' NW 1/16 S10 BT SCRIBED A 9" INCENSE CEDAR, N48°E, 22.7' NW 1/16 S10 BT</p>	<p>T26N R9E 1/4 S11 S11 S11 1973</p> <p>CORNER No. 27 FD. A BLM BCIP IN A MOUND OF STONE. CORNER FALLS ON A STEEP NORTHWEST SLOPE WEST OF A SPUR. FD. A 18" DOUGLAS FIR, S64°W, 7.9' -HB REC. A 14" DOUGLAS FIR, S69°W, 12 LKS (BLM) FD. A 9" DOUGLAS FIR, S78°E, 11.2' -HB REC. A 6" DOUGLAS FIR, S78°E, 17 LKS (BLM) FD. A 33" INCENSE CEDAR, S26°E, 9.9' -HB REC. A 29" CEDAR, S23°E, 14 LKS (BLM)</p>
<p>LS 2322</p> <p>CORNER No. 3 FD. A 1" IRON PIPE IN A MOUND OF STONE PER 1 R/S 97. CORNER FALLS ON A MODERATE NORTHEAST SLOPE 10°± WEST OF AN OLD ROAD. FD. A 12" WHITE FIR, S19°E, 11.5' HB NO REC. FD. A STUMPHOLE, S78°W, 8.8' REC. AN 4" FIR, S78°W, 8.8' (1 R/S 97)</p>	<p>T26N R9E S4 S3 S9 S10 1967</p> <p>CORNER No. 9 FD. A BLM BCIP IN A MOUND OF STONE. CORNER FALLS ON A STEEP NORTHEAST SLOPE IN HEAVY TIMBER, 160°± SOUTH OF A ROAD. FD. A 16" INCENSE CEDAR, N4°W, 43.6' -VS REC. A 15" CEDAR, N4°W, 66 LKS (BLM) FD. A 19" INCENSE CEDAR, N69°W, 25.5' -HB REC. A 14" CEDAR, N71°W, 26.4' (1 R/S 97) FD. A PINE SNAG, S72°E, 27.1' -VS REC. A 24" PINE S71°E, 27.0' (1 R/S 97) FD. DEAD AND DOWN OAK, S16°W, 31.7' REC. AN 18" OAK, S15°W, 31.6' (1 R/S 97) FD. A 31" PONDEROSA PINE, N68°E, 21.0' -HB REC. AN 18" PINE N68°E, 21.0' (1 R/S 97)</p>	<p>1/4 S2 S11 S11</p> <p>CORNER No. 14 FD. A 5" X 5" POST SCRIBED "MCL 8 6260" IN A MOUND OF STONE PER 3 RS 46. CORNER FALLS ON A GENTLE NORTH SLOPE AT THE SOUTHWEST CORNER OF A LOGGED AREA. NO BTS OF REC. OR MARKED</p>	<p>RCE 26870</p> <p>CORNER No. 21 FD. A 3/4" IRON PIPE TAGGED RCE 26870 IN A MOUND OF STONE PER 8 PM 64. CORNER FALLS ON AN EAST SLOPE IN TIMBER. FD. A TAGGED 9" WHITE FIR, S3°W, 6.0' NO REC. FD. A TAGGED 12" DOUGLAS FIR, N12°E, 9.0' NO REC.</p>	<p>1/4 S11 S11 S12</p> <p>CORNER No. 28 FD. A 1" IRON PIPE TAGGED LS 3202 (3/4" IP PER 5 PM 132) IN A MOUND OF STONE. CORNER FALLS ON A STEEP NORTH SLOPE IN HEAVY TIMBER. FD. A 24" WHITE FIR, S56°E, 43.6' HB NO REC. FD. A 27" WHITE FIR, S42°W, 9.9' HB NO REC.</p>
<p>T26N R9E S6 S5 S7 S8 1977 CAF USFS</p> <p>CORNER No. 4 FD. A CAF CAP IN A MOUND OF STONE. CORNER FALLS IN A MODERATE NORTHWEST SLOPE IN TIMBER AND BRUSH. FD. A TAGGED 10" WHITE FIR, S19 3/4°E, 22.4' NO REC. FD. A TAGGED 19" SUGAR PINE, N67 1/2°E, 24.4' NO REC. SCRIBED A 14" SUGAR PINE, S89°E, 12.8' "T26N R9E S8 BT" SCRIBED AN 8" DOUGLAS FIR, N41°W, 7.5' "T26N R9E S6 BT"</p>	<p>W 1/16 S3 S10 LS 4753 2008</p> <p>CORNER No. 10 SET A USFS DRIVE IN MONUMENT IN A MOUND OF STONE FROM WHICH A 1" IRON PIPE MKD LS 2322 (1 R/S 97) BEARS N30°W, 1.5'. CORNER FALLS ON A STEEP NORTHWEST SLOPE IN TIMBER. SCRIBED A 7" WHITE FIR, S63°W, 14.1' "W 1/16 S10 BT" SCRIBED A 9" INCENSE CEDAR, N41 3/4°W, 12.6' "W 1/16 S3 BT"</p>	<p>N 1/16 S7 S8 LS 4753 2008</p> <p>CORNER No. 16 SET A USFS DRIVE IN MONUMENT IN A MOUND OF STONE. CORNER FALLS ON A MODERATE SOUTH-SLOPE IN LIGHT TIMBER, 80°± SOUTH OF A ROAD. SCRIBED A 17" PONDEROSA PINE, N66°W, 61.3' "N 1/16 S7 BT" SCRIBED A 5" PINE, N86°E, 50.3' "N 1/16 S8 BT"</p>	<p>T26N R9E 1/4 S7 S7 S8 LS 4753 2008</p> <p>CORNER No. 23 NOTHING FD. SET A USFS DRIVE IN MONUMENT IN A MOUND OF STONE. CORNER FALLS ON A MODERATE NORTH SLOPE IN MODERATE TIMBER, 60°± FROM TOE OF SLOPE. SCRIBED AN 8" WHITE FIR, N65°E, 20.0' "1/4 S8 BT" SCRIBED A 6" CEDAR, N62°W, 14.0' "1/4 S7 BT"</p>	<p>1/16 S8 S8 S9 LS 4753 2008</p> <p>CORNER No. 30 SET A USFS DRIVE IN MONUMENT IN A MOUND OF STONE. CORNER FALLS ON A MODERATE SOUTH SLOPE IN MODERATE TIMBER. SCRIBED A 10" WHITE FIR, N12°W, 16.6' "S 1/16 S8 BT" SCRIBED AN 11" WHITE FIR, S62°W, 30.0' "S 1/16 S8 BT"</p>
<p>T26N R9E 1/4 S5 S8 LS 4753 2008</p> <p>CORNER No. 5 ORIG. STONE PER USFS CORNER RECORD E-7, 11-10-71 NOT FD. SET A USFS DRIVE IN MONUMENT IN A MOUND OF STONE. CORNER FALLS ON A FLAT NEAR THE TOP OF A SPUR IN CEDARS. SCRIBED AN 11" INCENSE CEDAR, S56°E, 3.4' "1/4 S8 BT" SCRIBED A 12" INCENSE CEDAR, N38 1/2°E, 26.5' "1/4 S5 BT"</p>	<p>CORNER No. 11 FD. A 1/2" IRON PIPE TAGGED LS 2322 PER 1 R/S 97 IN A MOUND OF STONE. CORNER FALLS ON A STEEP SOUTHEAST SLOPE AT THE EDGE OF A CLEAR CUT, 300°± WEST OF A ROAD. FD. A 25" DOUGLAS FIR, N61°E, 6.6' -HB REC. A 16" FIR, N60°E, 6.6' (1 R/S 97) FD. A 20" PONDEROSA PINE, S3°W, 14.5' -HB REC. A 14" PINE, S5°W, 15.1' (1 R/S 97)</p>	<p>C N 1/16 S8 C LS 4753 2008</p> <p>CORNER No. 17 SET A USFS DRIVE IN MONUMENT IN A MOUND OF STONE. CORNER FALLS ON A MODERATE SOUTHEAST SLOPE IN LARGELY CEDAR TIMBER. SCRIBED AN 8" DOUGLAS FIR, S78°E, 3.9' "CN 1/16 S8 BT" SCRIBED A 9" PONDEROSA PINE, S18°W, 8.3' "CN 1/16 S8 BT"</p>	<p>T26N R9E C 1/4 S8 LS 4753 2008</p> <p>CORNER No. 24 SET A USFS DRIVE IN MONUMENT IN A MOUND OF STONE. CORNER FALLS ON A MODERATE SOUTH-SLOPE IN SPARSE TIMBER. SCRIBED A 31" SUGAR PINE, N60°E, 10.0' "C 1/4 S8 BT" SCRIBED AN 11" PONDEROSA PINE, S20°W, 21.1' "C 1/4 S8 BT"</p>	<p>1/16 S12 S12 S12 LS 4753 2008</p> <p>CORNER No. 31 SET A USFS DRIVE IN MONUMENT IN A MOUND OF STONE. CORNER FALLS ON A STEEP NORTH SLOPE. SCRIBED A 5" DOUGLAS FIR, N48°W, 8.4' "X BT" SCRIBED A 5" DOUGLAS FIR, N32°E, 4.2' "X BT"</p>
<p>E 1/16 S5 S8 LS 4753 2008</p> <p>CORNER No. 6 SET A USFS DRIVE IN MONUMENT IN A MOUND OF STONE. CORNER FALLS ON A STEEP NORTH SLOPE. SCRIBED A 5" DOUGLAS FIR, N72°W, 31.1' "X BT" NO OTHER TREES AVAILABLE</p>	<p>T26N R9E S3 S2 S10 S11 1973</p> <p>CORNER No. 12 FD. A BLM BCIP IN A MOUND OF STONE. CORNER FALLS ON A STEEP NORTHEAST SPUR IN TIMBER, PER 8 PM 64. FD. A 4" SUGAR PINE, N60°W, 6.9' -HB REC. A 7" SUGAR PINE, N59°W, 16 LKS (BLM) FD. A 21" SUGAR PINE, N39°E, 26.4' -HB REC. A 13" SUGAR PINE, N39°E, 40 LKS (BLM) FD. A 40" PINE SNAG, S14 1/2°W, 26.1' -VS REC. A 36" YELLOW PINE, S13 1/2°W, 23.3' (8 PM 64) FD. A 14" DOUGLAS FIR, S50°E, 24.1' -HB REC. A 10" DOUGLAS FIR, S50°E, 37 LKS (BLM)</p>	<p>C N 1/16 S9 C LS 4753 2008</p> <p>CORNER No. 18 SET A USFS DRIVE IN MONUMENT IN A MOUND OF STONE. CORNER FALLS ON A STEEP EAST SLOPE IN TIMBER. SCRIBED A 7" DOUGLAS FIR, N22°W, 16.1' "X BT" SCRIBED AN 8" DOUGLAS FIR, N74°W, 10.2' "CN 1/16 S9 BT"</p>	<p>T26N R9E 1/4 S8 S8 S9 LS 4753 2007</p> <p>CORNER No. 25 SET BY SINGLE PROPORTION SET A USFS DRIVE IN MONUMENT IN A MOUND OF STONE. CORNER FALLS ON A STEEP NORTHEAST SLOPE IN TIMBER, 70°± EAST OF A RIDGE. FD. A SUGAR PINE SNAG, S68 1/2°E, 27.7' REC. 48" SUGAR PINE S68 1/2°E, 27.7' GLO SCRIBED AN 11" WHITE FIR, S54°E, 13.4' "1/4 S9 BT" SCRIBED A 9" INCENSE CEDAR, S23°W, 9.6' "1/4 S8 BT"</p>	<p>USDA FOREST SERVICE PLUMAS NATIONAL FOREST "KEEDIE"</p>
<p>T26N R9E S5 S4 S8 S9 1977 CAF USFS</p> <p>CORNER No. 7 FD. A CAF CAP IN A MOUND OF STONE. CORNER FALLS ON A STEEP NORTHEAST SLOPE IN TIMBER. FD. A 50" PINE SNAG, N30°W, 64.0' REC. A 57" SUGAR PINE, N30 1/2°W, 97 LKS. (USFS CR E-9 11-2-72) FD. A FIR STUMP, N35°E, 21.6' REC. A 51" WHITE FIR, N35°E, 32 LKS. (USFS CR E-9 11-2-72) FD. A TAGGED 13" INCENSE CEDAR, S66°W, 10.2' NO REC. SCRIBED AN 11" INCENSE CEDAR, S16°E, 16.7' "T26N R4 E S9 BT"</p>	<p>W 1/16 S2 S11 LS 4753 2008</p> <p>CORNER No. 13 SET A USFS DRIVE IN MONUMENT IN MOUND OF STONE FROM WHICH A 3/4" IRON PIPE MKD LS 3297 NO REC. BEARS N25°W, 0.72'. CORNER FALLS ON A GENTLE NORTH SLOPE OF A RIDGE ON THE WEST EDGE OF A ROAD. SCRIBED A 14" WHITE FIR, S28°E, 29.1' "W 1/16 S11 BT" SCRIBED A 9" PONDEROSA PINE, N26°E, 62.6' "W 1/16 S2 BT"</p>	<p>N 1/16 S9 S9 S10 LS 4753 2008</p> <p>CORNER No. 19 SET A USFS DRIVE IN MONUMENT IN A MOUND OF STONE. CORNER FALLS ON A MODERATE SOUTHEAST SLOPE, 75°± NORTHWEST OF AN OLD ROAD. SCRIBED A 7" DOUGLAS FIR, N34°W, 9.4' "N 1/16 S9 BT" SCRIBED A 5" DOUGLAS FIR, N53°E, 30.0' "X BT"</p>	<p>T26N R9E 1/4 S9 S9 S10 1973</p> <p>CORNER No. 26 FD. A BLM BCIP IN A MOUND OF STONE. CORNER FALLS ON A STEEP SOUTHEAST SLOPE, 40°± NORTH OF A ROAD. FD. AN 11" WHITE FIR, S61°E, 25.1' -HB REC. A 10" DOUGLAS FIR, S61°E, 38 LKS (BLM) FD. A 15" WHITE FIR, N67°W, 37.6' REC. AN 8" WHITE FIR, N67°W, 57 LKS (BLM)</p>	<p>DATE: NOVEMBER, 2008 SHEET 6 OF 8</p>

